



**27" Full HD IPS monitor with edge-to-edge design, perfect for multi-monitor setups with height adjustable stand**

Stylish edge-to-edge design makes the ProLite XUB2793HS perfect for multi-monitor set-ups. The IPS panel technology offers accurate and consistent colour reproduction with wide viewing angles. High contrast and brightness values mean the monitor will provide excellent performance for photographic and web design. Equipped with speakers, headphone socket, HDMI and DisplayPort connections, a blue light reducer function to reduce eye fatigue and an ergonomic 150mm height adjustable stand for optimal user comfort make this 27" monitor a great choice for both multi-monitor configuration and office applications.

Available also with fixed stand : [ProLite XU2793HS-B5 \(1920x1080\)](#) and [ProLite XU2793HS-B6 \(1920x1080\)](#)



**IPS Technology**

IPS technology offers higher contrast, darker blacks and much better viewing angles than standard TN technology. The screen will look good no matter what angle you look at it.



**HAS (150mm) + PIVOT**

With a height adjustable stand you will create an ergonomic work posture and position that meets all health and safety requirements. This will not only prevent any health issues but will also increase your productivity. The pivot function allows the screen to rotate from landscape to portrait orientation. This functionality can be useful if the application requires more height than width.

## 01 DISPLAY CHARACTERISTICS

|                      |                                            |
|----------------------|--------------------------------------------|
| Design               | 3-side borderless                          |
| Diagonal             | 27", 68.6cm                                |
| Panel                | IPS panel technology LED, matte finish     |
| Native resolution    | 1920 x 1080 @100Hz (2.1 megapixel Full HD) |
| Aspect ratio         | 16:9                                       |
| Panel brightness     | 250 cd/m <sup>2</sup>                      |
| Static contrast      | 1000:1                                     |
| Advanced contrast    | 80M:1                                      |
| Response time (MPRT) | 1ms                                        |
| Colour support       | 16.7mIn (sRGB: 96%; NTSC: 72%)             |
| Horizontal Sync      | 30 - 110kHz                                |
| Viewable area W x H  | 597.9 x 336.3mm, 23.5 x 13.2"              |
| Pixel pitch          | 0.311mm                                    |
| Colour               | matte, black                               |

## 02 INTERFACES / CONNECTORS / CONTROLS

|                     |                           |
|---------------------|---------------------------|
| Signal input        | HDMI x1<br>DisplayPort x1 |
| HDCP                | yes                       |
| Headphone connector | yes                       |

## 03 FEATURES

|                       |                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Blue light reducer    | yes                                                                                                                                                                                                                                                                                                                                                                                          |
| Flicker free          | yes                                                                                                                                                                                                                                                                                                                                                                                          |
| Adaptive Sync support | yes                                                                                                                                                                                                                                                                                                                                                                                          |
| Extra                 | i-style Colour                                                                                                                                                                                                                                                                                                                                                                               |
| OSD languages         | EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL                                                                                                                                                                                                                                                                                                                                                       |
| Control buttons       | Power, Menu, Up / Right / Volume, Down / Left / i-Style colour, Input / Exit                                                                                                                                                                                                                                                                                                                 |
| User controls         | picture adjust (brightness, contrast, Eco, ACR, OD, MBR, Adaptive Sync), colour settings (i-Style colour, blue light reducer, colour temp., user preset), OSD (H. position, V. position, OSD rotate, OSD time), language, recall, miscellaneous (sharp and soft, video mode adjust, opening logo, RGB range, LED, display information), input select (source), audio settings (volume, mute) |
| Speakers              | 2 x 2W                                                                                                                                                                                                                                                                                                                                                                                       |
| Convenience           | Kensington-lock™ prepared, DDC/CI, DDC2B, Mac OSX                                                                                                                                                                                                                                                                                                                                            |

## 04 MECHANICAL

|                              |                                                   |
|------------------------------|---------------------------------------------------|
| Display position adjustments | height, swivel, tilt, pivot (rotation both sides) |
| Height adjustment            | 150mm                                             |
| Rotation (PIVOT function)    | 90°                                               |
| Swivel stand                 | 90°; 45° left; 45° right                          |
| Tilt angle                   | 23° up; 5° down                                   |
| VESA mounting                | 100 x 100mm                                       |
| Cable management system      | yes                                               |

## 05 ACCESSORIES INCLUDED

|               |                                 |
|---------------|---------------------------------|
| <b>Cables</b> | power, HDMI                     |
| <b>Other</b>  | quick start guide, safety guide |

## 06 POWER MANAGEMENT

|                          |                                           |
|--------------------------|-------------------------------------------|
| <b>Power supply unit</b> | internal                                  |
| <b>Power supply</b>      | AC 100 - 240V, 50/60Hz                    |
| <b>Power usage</b>       | 22W typical, 0.5W stand by, 0.3W off mode |

## 07 SUSTAINABILITY

|                                                            |                                                                                       |
|------------------------------------------------------------|---------------------------------------------------------------------------------------|
| <b>Regulations</b>                                         | TCO Certified, CE, TÜV-Bauart, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA |
| <b>Energy efficiency class (Regulation (EU) 2017/1369)</b> | E                                                                                     |
| <b>REACH SVHC</b>                                          | above 0.1%: Lead                                                                      |

## 08 DIMENSIONS / WEIGHT

|                                     |                                 |
|-------------------------------------|---------------------------------|
| <b>Product dimensions W x H x D</b> | 611.5 x 400.5 (550.5) x 209.5mm |
| <b>Box dimensions W x H x D</b>     | 736 x 434 x 187mm               |
| <b>Weight (without box)</b>         | 5.4kg                           |
| <b>Weight (with box)</b>            | 8.4kg                           |
| <b>EAN code</b>                     | 4948570124084                   |

*All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.*

© IIYAMA CORPORATION. ALL RIGHTS RESERVED