

Ex d Cable Gland M20 Non-armored

Cable gland for non-armored cables hazardous areas

For hazardous area compliance of maintaining a secure connection where the non-armored cable connects to the camera or junction box. The Ex d cable gland is certified for flameproof enclosures. The cable gland suits cable entries with M20x1.5 threads.

> [Certified for ATEX, IECEx](#)



Ex d Cable Gland M20 Non-armored

General			
Supported products	Non-armored cables ExCam, 10, 25, 95 m (33, 82, 312 ft)	ATEX: II 2 G Ex d IIC Gb, II 1 D Ex ta IIIC Da Certi cate: SIRA 13 ATEX 1072 X IECEX: Ex d IIC Gb, Ex ta IIIC Da Certi cate: IECEX SIR 13.0027X -60°C < Tamb < +85°C	
Cable routing	For cable diameter: 6.5–14.0 mm (0.26–0.55 in) Thread length: 15 mm (0.6 in)	Included accessories	Documentation
Casing	Nickel-plated brass Color: Metal/silver/red	Environmental responsibility: axis.com/environmental-responsibility	
Approvals	Environment: IEC/EN 60529 IP66, IP67, IP68 Explosion: EN/IEC 60079-0, EN/IEC 60079-1, EN/IEC 60079-7, EN/IEC 60079-31		
Certi cations	Model key: Cable gland type PXSS2K		