



C R E

A T E



PUSHING THE BOUNDARIES OF TECHNOLOGIES AND INNOVATION

ATOMX SSDmini DELIVERS PROFESSIONAL GRADE RECORDING MEDIA IN A REDUCED SSD FORM FACTOR. GET THE SAME ROBUST, RELIABLE, HIGH PERFORMANCE OF OUR TRADITIONAL SATA SSD MEDIA - BUT SMALLER. ATOMX SSDmini GIVES YOU THE CONFIDENCE TO PUSH YOUR CREATIVE POTENTIAL.

A
t
o
m
X

S
S
D
m
i
n
i

SPECIFICATIONS AND FEATURES



Developed for ATOMOS

NINJA V | NINJA FLAME | NINJA INFERNO |
SUMO 19* | SUMO 19M* | SHOGUN FLAME |
SHOGUN INFERNO | SHOGUN STUDIO*



ESD & Overload Protection

Protection from on-the-job electrostatic discharge.



Speed

| | Read | Write |
|------------|----------|----------|
| Sustained | 540 MB/s | 500 MB/s |
| Sequential | 560 MB/s | 520 MB/s |



Solid Grip™, Shock & Temperature Proof



500 GB | 1 TB | 2 TB



Power Smoothing



4k60p 2k240p Apple ProRes / Avid DNx
5.7k30p 4k60p 2k240p Apple ProRes RAW
4k30p CDNG



CNC-Worked Aluminium Casing



Stable Stream™

Stable, sustained performance that ensures high-def quality and smooth video recording in RAW or compressed formats.



Rock-Solid Build



X-Ray & Magnetic Proof



Data Recovery

Angelbird's professional technicians will evaluate any physical damage or file corruption and safely attempt an in-office, secure data-recovery

MATCH PACK™

SPECIFICATIONS / ORDERING

A
t
o
m
X
S
S
D
m
i
n
i

GENERAL SPECIFICATIONS

Capacity
500 GB | 1 TB | 2 TB

Dimensions
80 × 75.5 × 9.3 mm
(3.15 × 2.97 × 0.37 in)

Form Factor
SSDmini

Weight
~ 90.0g | ~3.17 oz

TECHNICAL SPECIFICATIONS

Interface
SATA 6 Gb/s, 3 Gb/s and 1.5 Gb/s supported
SATA 3.0 compliant

Over provisioning
~ 9 %

Features
Temperature sensor, overload protection, TRIM, ECC, EMS protection, built-in cache, SMART, NCQ

PERFORMANCE SPECIFICATIONS

Sustained Read Speed¹
up to 540 MB/s
Sustained Write Speed¹
up to 500 MB/s

Sequential Read Speed¹
up to 560 MB/s
Sequential Write Speed¹
up to 520 MB/s

Access Time (R/W)
~ 65 µs / 40 µs

RELIABILITY SPECIFICATIONS

MTBF
> 2,400,000 hours

Data Reliability
Built-in EDC | ECC function

Data Retention
10 years at 25 °C

Endurance
500 GB: 1,500 TBW
1 TB: 3,000 TBW
2 TB: 6,000 TBW

Certifications
RoHS, FCC and CE compliant, REACH

ELECTRICAL SPECIFICATIONS

DC input voltage
5 V ± 10 %

Power usage (idle | max)
500 GB: 0.35 W | 3.0 W
1 TB: 0.35 W | 3.5 W
2 TB: 0.35 W | 3.5 W

ENVIRONMENTAL SPECIFICATIONS

Shock resistance (operating)
1000 G/0.5ms

Vibration resistance (operating)
2.17 G_{RMS}

Operating Temperature
-20 °C | 70 °C

Storage Temperature
-40 °C | 85 °C

Operating Humidity
5 % to 95 % non-condensing

COMPATIBLE WITH³

NINJA V
NINJA FLAME
NINJA INFERNO
SUMO 19*
SUMO 19M*
SHOGUN FLAME
SHOGUN INFERNO
SHOGUN STUDIO*
*only with Atomos SSDmini Adapter

WARRANTY²

3-Year Limited Warranty
or TBW threshold exceeded

PACKAGE CONTENT

- AtomX SSDmini
- Activation code for the full limited warranty

RETAIL PACKAGING DETAILS

Box Dimension
125.0 × 112.0 × 20.0 mm
(4.92 × 4.41 × 0.79 in)

Weight
~ 120.0g | ~4.2 oz

¹ Speed based on internal testing. Actual transfer rates and capacity may vary depending on the product model, system hardware and other factors.

² To receive the full limited warranty, the product needs to be registered on the Angelbird Personal Service Portal within 30 days after purchase. If not registered within this period, the market-specific legal guarantee period comes into force.

³ For an up-to-date compatibility list, please visit the product site at www.angelbird.com

Atomos® is a registered trademark of Atomos Global Pty. Ltd. Match Pack™ is a trademark of Angelbird Technologies GmbH.

Other product names used herein are for identification purposes only and may be trademarks of their respective owners. Angelbird disclaims any and all rights in those marks.

ORDERING INFORMATION

| Capacity | SKU | EAN | UPC |
|----------|-----------------|---------------|--------------|
| ● 500 GB | ATOMXMINI500PK | 9120056584185 | 812937023003 |
| ● 1 TB | ATOMXMINI1000PK | 9120056584192 | 812937023010 |
| ● 2 TB | ATOMXMINI2000PK | 9120056584376 | 812937023195 |

MATCH PACK™