



C R E

A T E



# PUSHING THE BOUNDARIES OF TECHNOLOGIES AND INNOVATION

ATOMX SSDmini DELIVERS PROFESSIONAL GRADE RECORDING MEDIA IN A REDUCED SSD FORM FACTOR. GET THE SAME ROBUST, RELIABLE, HIGH PERFORMANCE OF OUR TRADITIONAL SATA SSD MEDIA - BUT SMALLER. ATOMX SSDmini GIVES YOU THE CONFIDENCE TO PUSH YOUR CREATIVE POTENTIAL.

A  
t  
o  
m  
X  
  
S  
S  
D  
m  
i  
n  
i

## SPECIFICATIONS AND FEATURES



### Developed for ATOMOS

NINJA V | NINJA FLAME | NINJA INFERNO |  
SUMO 19\* | SUMO 19M\* | SHOGUN FLAME |  
SHOGUN INFERNO | SHOGUN STUDIO\*



### ESD & Overload Protection

Protection from on-the-job electrostatic discharge.



### Speed

	Read	Write
Sustained	540 MB/s	500 MB/s
Sequential	560 MB/s	520 MB/s



### Solid Grip™, Shock & Temperature Proof



500 GB | 1 TB | 2 TB



### Power Smoothing



4k60p 2k240p Apple ProRes / Avid DNx  
5.7k30p 4k60p 2k240p Apple ProRes RAW  
4k30p CDNG



### CNC-Worked Aluminium Casing



### Stable Stream™

Stable, sustained performance that ensures high-def quality and smooth video recording in RAW or compressed formats.



### Rock-Solid Build



### X-Ray & Magnetic Proof



### Data Recovery

Angelbird's professional technicians will evaluate any physical damage or file corruption and safely attempt an in-office, secure data-recovery

MATCH PACK™

# SPECIFICATIONS / ORDERING

A  
t  
o  
m  
X  
S  
S  
D  
m  
i  
n  
i

## GENERAL SPECIFICATIONS

Capacity  
500 GB | 1 TB | 2 TB

Dimensions  
80 × 75.5 × 9.3 mm  
(3.15 × 2.97 × 0.37 in)

Form Factor  
SSDmini

Weight  
~ 90.0g | ~3.17 oz

## TECHNICAL SPECIFICATIONS

Interface  
SATA 6 Gb/s, 3 Gb/s and 1.5 Gb/s supported  
SATA 3.0 compliant

Over provisioning  
~ 9 %

Features  
Temperature sensor, overload protection, TRIM, ECC, EMS protection, built-in cache, SMART, NCQ

## PERFORMANCE SPECIFICATIONS

Sustained Read Speed<sup>1</sup>  
up to 540 MB/s  
Sustained Write Speed<sup>1</sup>  
up to 500 MB/s

Sequential Read Speed<sup>1</sup>  
up to 560 MB/s  
Sequential Write Speed<sup>1</sup>  
up to 520 MB/s

Access Time (R/W)  
~ 65 µs / 40 µs

## RELIABILITY SPECIFICATIONS

MTBF  
> 2,400,000 hours

Data Reliability  
Built-in EDC | ECC function

Data Retention  
10 years at 25 °C

Endurance  
500 GB: 1,500 TBW  
1 TB: 3,000 TBW  
2 TB: 6,000 TBW

Certifications  
RoHS, FCC and CE compliant, REACH

## ELECTRICAL SPECIFICATIONS

DC input voltage  
5 V ± 10 %

Power usage (idle | max)  
500 GB: 0.35 W | 3.0 W  
1 TB: 0.35 W | 3.5 W  
2 TB: 0.35 W | 3.5 W

## ENVIRONMENTAL SPECIFICATIONS

Shock resistance (operating)  
1000 G/0.5ms

Vibration resistance (operating)  
2.17 G<sub>RMS</sub>

Operating Temperature  
-20 °C | 70 °C

Storage Temperature  
-40 °C | 85 °C

Operating Humidity  
5 % to 95 % non-condensing

## COMPATIBLE WITH<sup>3</sup>

NINJA V  
NINJA FLAME  
NINJA INFERNO  
SUMO 19\*  
SUMO 19M\*  
SHOGUN FLAME  
SHOGUN INFERNO  
SHOGUN STUDIO\*  
\*only with Atomos SSDmini Adapter

## WARRANTY<sup>2</sup>

3-Year Limited Warranty  
or TBW threshold exceeded

## PACKAGE CONTENT

- AtomX SSDmini
- Activation code for the full limited warranty

## RETAIL PACKAGING DETAILS

Box Dimension  
125.0 × 112.0 × 20.0 mm  
(4.92 × 4.41 × 0.79 in)

Weight  
~ 120.0g | ~4.2 oz

<sup>1</sup> Speed based on internal testing. Actual transfer rates and capacity may vary depending on the product model, system hardware and other factors.

<sup>2</sup> To receive the full limited warranty, the product needs to be registered on the Angelbird Personal Service Portal within 30 days after purchase. If not registered within this period, the market-specific legal guarantee period comes into force.

<sup>3</sup> For an up-to-date compatibility list, please visit the product site at [www.angelbird.com](http://www.angelbird.com)

Atomos® is a registered trademark of Atomos Global Pty. Ltd. Match Pack™ is a trademark of Angelbird Technologies GmbH.

Other product names used herein are for identification purposes only and may be trademarks of their respective owners. Angelbird disclaims any and all rights in those marks.

## ORDERING INFORMATION

Capacity	SKU	EAN	UPC
● 500 GB	ATOMXMINI500PK	9120056584185	812937023003
● 1 TB	ATOMXMINI1000PK	9120056584192	812937023010
● 2 TB	ATOMXMINI2000PK	9120056584376	812937023195

MATCH PACK™