



100% recycled material used for external cassette



+40% of DYMO® labels are produced\* using „Water based solvents“.





DYMO® high quality labels are made in Belgium



## D1 Standard Polyester Labels

For hundreds of tasks around the office or home office, such as filing, storage and asset tracking.  
Temperature rating: -18°C to 90°C

D1 STANDARD LABELS (7 m)	6 mm	9 mm	12 mm	19 mm
ABC	S0720780	S0720680	S0720530	S0720830
ABC	S0720770	S0720670	S0720500	S0720820
ABC	S0720790	S0720730	S0720580	S0720880
ABC	-	S0720710	S0720560	S0720860
ABC	-	S0720740	S0720590	S0720890
ABC	-	S0720720	S0720570	S0720870
ABC	-	-	S0720610	S0720910
ABC	-	S0720690	S0720540	S0720840
ABC	-	-	S0720510	-
ABC	-	-	S0720600	-
ABC	-	S0720700	S0720550	S0720850
ABC	-	-	S0720520	-
D1 STANDARD MULTIPACKS (7 m)	6 mm	9 mm	12 mm	19 mm
ABC	-	2093096	2093097	2093098



## D1 Durable Vinyl Labels

Industrial strength adhesive helps to ensure labels stay stuck to a variety of surfaces.  
Temperature rating: -40°C to 80°C

D1 DURABLE LABELS (3 m)	12 mm
ABC	1978366
ABC	1978365
ABC	1978367
D1 DURABLE LABELS (5.5 m)	12 mm
ABC	1978364



## D1 Permanent Polyester Labels

Professional, polished finish ideal for panels, blocks, faceplates, shelves, bins and more.  
Temperature rating: -40°C to 150°C\*

D1 PERMANENT POLYESTER (5.5 m)	12 mm	19 mm
ABC	S0718060	S0718050

\*depends on surface



## D1 Flexible Nylon Labels

Specifically designed for curved surfaces and wire and cable marking.  
Temperature rating: -40°C to 60°C

D1 FLEXIBLE NYLON (3.5 m)	12 mm	19 mm
ABC	S0718040	S0718070



The DYMO® high quality labels are made in Belgium



© 2021 Newell Brands

This information is being provided for general information purposes and the compliance standards and certifications referenced herein are based on current standards which are subject to change.

