


## Sony SRG-X40UH Dome IP security camera Indoor 3840 x 2160 pixels Ceiling/wall

Brand : Sony Product code: SRG-X40UH/WC

Product name: SRG-X40UH







Makement supported   Indoor   Supported yielgnites resolutions   (Ho 1080), 3860 x 2160   Yenometrivity technology   Wired   Supported video modes   720p, 1080i, 1080p, 2160p   Yenometrivity technology   Wired   Noise reduction   Yenometricity   ZD noise reduction, 3D noise reduction   Yenometricity   ZD noise reduction   ZD noise   ZD noise reduction   ZD noise   ZD noise reduction   ZD noise   ZD noise reduction   ZD noise reduction   ZD noise   ZD noise	Performance		Video	
Noise reduction  Noise reduction  Noise reduction  Noise reduction  Noise reduction  Noise reduction technology  applyinght mode  Auto, Manual  Auto, Manual	Type * Placement supported * Connectivity technology *	Indoor	5 .	(HD 1080), 3860 x 2160
Infrared (IR) cut-off filter         √         Noise reduction technology         2D noise reduction, 3D noise reduction, and noise reduction manages as proport         Auto, Manual manages as proport         2D noise reduction, and noise reduction, and noise reduction manages support         Auto, Manual manages as proport         Auto/Manual manages as proport	, ,,		• •	• • • • • • • • • • • • • • • • • • • •
Light exposure modes         Auto, Manual mage stabilizer         Auto, M	Infrared (IR) cut-off filter	✓	Noise reduction technology	
Image stabilizer   Metwork   Metwo	Light exposure modes	,	Gain control type	
Network   Stemme		Multi	Image stabilizer	✓
Adounting type * Ceiling/wall White White White White White Wi-Fi * X**  Amera  Amera  Camera pan control	Design		Network	
Networking standards   IEEE 802.3at			Ethernet LAN *	✓
Amera pan control  Anti-micra ports  Anti-micra ports  Anti-micra ports  Anti-micra  Anti	5 7.	-	•	
Storage Camera pan control Camera tilt control Camera sped			Wi-Fi *	×
Adminimum illumination 1.6 lx Ports & interfaces Lens viewing angle, horizontal 70° Ethernet LAN (RJ-45) ports 1 Lift angle range 20 - 90° RS-422 ports 2 Lan range 126 °/sec USB port 4 Lan range 1770 - 170° HDMI ports quantity 1 Lan speed 300 °/sec Security  White balance Auto, Indoor, Manual, One push, Outdoor Lanera shutter speed 0,0001 - 1 s Power  Lamera shutter speed 0,000 - 1 s Power  Lamera shutter spe		1	Storage	
Ethernet LAN (RJ-45) ports 1 filt angle range -20 -90° RS-422 ports 2 filt speed 126 °/sec USB port	Camera tilt control		Built-in HDD *	×
Filt angle range	Minimum illumination	1.6 lx	Ports & interfaces	
Tilt speed 126 °/sec USB port	Lens viewing angle, horizontal			
Pan range any	Tilt angle range			
Auto, Indoor, Manual, One push, Outdoor  Anti-flicker  Actionut type *  Actionut voltage  Anti-flicker  Actionut voltage  Anti-flicker  Actionut voltage  Anti-flicker  Actionut frequency  50-PoE  60-PoE  60-P	•	•	•	
Auto, Indoor, Manual, One push, Outdoor  Camera shutter speed  O.0001 - 1 s  Power  Power  Power source type * DC, PoE  Act input voltage 100 - 240 V  Act input frequency 50/60 Hz  Power consumption (max) 25.5 W  CMOS Power consumption (max) 25.5 W  Common capability Common 20x  Co	Pan speed			-
Camera shutter speed 0.0001 - 1 s Power  Power source type * DC, PoE  Aumber of sensors 1 AC input voltage 100 - 240 V  AC input frequency 50/60 Hz  Power consumption (max) 25.5 W  DC output voltage 12  Com capability V  Com capability V  Operational conditions  Complicial zoom 20x  Operating temperature (T-T) 0 - 40 °C  Storage temperature (T-T) - 20 - 60 °C  Number of lenses * 1  Weight & dimensions  Video  Video  Video  Video  Video formats supported  M-JPEG  Power source type *  AC input voltage 100 - 240 V  AC input frequency 50/60 Hz  Power consumption (max) 25.5 W  DC output voltage 12  Operational conditions  Very complete to 12  Operational conditions  Very complete to 12  Operational conditions  Very complete to 12  Operational conditions  Operating temperature (T-T) 0 - 40 °C  Storage temperature (T-T) - 20 - 60 °C  Very complete to 158.4 mm  Video  Very complete to 177.5 mm  Height 200.2 mm  Video formats supported  M-JPEG  Packaging content	White balance		•	.1
Power source type * DC, PoE  Number of sensors 1 AC input voltage 100 - 240 V AC input frequency 50/60 Hz  Power consumption (max) 25.5 W  DC output voltage 12  Come capability Coptical zoom 20x  Storage temperature (T-T) 0 - 40 °C  Storage temperature (T-T) - 20 - 60 °C  Number of lenses * 1  Weight & dimensions  Video  Maximum resolution * 3840 x 2160 pixels  Total megapixels * 8.5 MP  Weight Content				•
AC input voltage 100 - 240 V Optical sensor size 25.4 / 2.5 mm (1 / 2.5") AC input frequency 50/60 Hz Sensor type * CMOS Power consumption (max) 25.5 W Optical sensor size 12 Coom capability Optical zoom 20x Operating temperature (T-T) 0 - 40 °C Opigital zoom 40x Storage temperature (T-T) -20 - 60 °C Output voltage 15 Storage temperature (T-T) -20 - 60 °C Operating temperature (T-T) -20 - 60 °C Operatin	·	0.0001 - 1 3		DC PoE
AC input frequency 50/60 Hz  Spensor type * CMOS Power consumption (max) 25.5 W  Lens system  Coom capability Optical zoom 20x Operating temperature (T-T) 0 - 40 °C  Storage temperature (T-T) -20 - 60 °C  Number of lenses * 1  Weight & dimensions  Video  Asximum resolution * 3840 x 2160 pixels  M-JPEG  AC input frequency 50/60 Hz  Power consumption (max) 25.5 W  DC output voltage 12  Operational conditions  1  Very display to the properature (T-T) 0 - 40 °C  Storage temperature (T-T) -20 - 60 °C  Weight & dimensions  Vidth 158.4 mm  Depth 177.5 mm  Height 200.2 mm  Weight & 200.2 mm  Very display to the properation of the properatio	•	1		
Sensor type * CMOS  Power consumption (max) 25.5 W  DC output voltage 12  Coom capability  Operational conditions  Operating temperature (T-T) 0 - 40 °C  Storage temperature (T-T) -20 - 60 °C  Number of lenses * 1  Cocal length range 4.4 - 88 mm  Width 158.4 mm  Opeth 177.5 mm  Maximum resolution * 3840 x 2160 pixels  Total megapixels * 8.5 MP  Weight Cormats supported  M-JPEG  Power consumption (max) 25.5 W  DC output voltage 12  Deprational conditions  Very deprature (T-T) 0 - 40 °C  Storage temperature (T-T) -20 - 60 °C  Weight & dimensions  Width 158.4 mm  177.5 mm  Height 200.2 mm  Weight 1.6 kg			· -	
Toom capability  Zoom capability  Zoon	Sensor type *		Power consumption (max)	25.5 W
Coom capability✓Operational conditionsOptical zoom20xOperating temperature (T-T)0 - 40 °CDigital zoom40xStorage temperature (T-T)-20 - 60 °CNumber of lenses *1Weight & dimensionsFocal length range4.4 - 88 mmWidth158.4 mmVideoDepth177.5 mmMaximum resolution *3840 x 2160 pixelsHeight200.2 mmTotal megapixels *8.5 MPWeight1.6 kgVideo formats supportedM-JPEGPackaging content	Lens system		DC output voltage	12
Operating temperature (T-T) 0 - 40 °C Origital zoom 40x Storage temperature (T-T) -20 - 60 °C Number of lenses * 1 Weight & dimensions Focal length range 4.4 - 88 mm Width 158.4 mm Depth 177.5 mm Maximum resolution * 3840 x 2160 pixels Fotal megapixels * 8.5 MP Weight Weight 1.6 kg  Packaging content	Zoom capability	✓	Operational conditions	
Number of lenses * 1 Weight & dimensions  Focal length range 4.4 - 88 mm Width 158.4 mm  Depth 177.5 mm  Maximum resolution * 3840 x 2160 pixels Height 200.2 mm  Total megapixels * 8.5 MP Weight 1.6 kg  M-JPEG Packaging content	Optical zoom	20x		• •
Focal length range 4.4 - 88 mm Width 158.4 mm  //ideo Depth 177.5 mm  //aximum resolution * 3840 x 2160 pixels Height 200.2 mm  Fotal megapixels * 8.5 MP Weight 1.6 kg  //ideo formats supported M-JPEG Packaging content	Digital zoom		Storage temperature (T-T)	-20 - 60 °C
Video     Depth     177.5 mm       Maximum resolution *     3840 x 2160 pixels     Height     200.2 mm       Fotal megapixels *     8.5 MP     Weight     1.6 kg       Video formats supported     M-JPEG     Packaging content	Number of lenses *		_	
Maximum resolution * 3840 x 2160 pixels Height 200.2 mm  Total megapixels * 8.5 MP Weight 1.6 kg  M-JPEG Packaging content		4.4 - 88 mm		
Total megapixels * 8.5 MP Weight 1.6 kg  Packaging content	Video			
/ideo formats supported M-JPEG Packaging content		•	•	
	Video formats supported		-	J
		-		1

## Packaging content

Cables included HDMI Mounting brackets included ✓



4548736141742

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.