

ASUS PRIME Z790-P WIFI D4 Intel Z790 LGA 1700 ATX

Brand: ASUS Product code: 90MB1DB0-M0EAY0

Product name: PRIME Z790-P WIFI D4

ASUS Prime Z790-P WIFI D4, an Intel Z790 LGA 1700 ATX motherboard with PCle® 5.0, three M.2 slots, 14+1 DrMOS, DDR4, Realtek 2.5Gb Ethernet, Intel® Wi-Fi 6, HDMI®, DP, USB 3.2 Gen 2x2 Type-C®, front USB 3.2 Gen 2 Type-C®, Thunderbolt™ (USB4®) support, Arua Sync ASUS PRIME Z790-P WIFI D4. Processor manufacturer: Intel, Processor socket: LGA 1700, Compatible processor series: Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9,.... Supported memory types: DDR4-SDRAM, Maximum internal memory: 128 GB, Memory slots type: DIMM. Supported storage drive interfaces: M.2, SATA III, Supported storage drive types: HDD & SSD, RAID levels: 0, 1, 5, 10. Ethernet interface type: 2.5 Gigabit Ethernet, Top Wi-Fi standard: Wi-Fi 6 (802.11ax), Wi-Fi standards: 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax). Component for: PC, Motherboard form factor: ATX, Motherboard chipset family: Intel





| Processor | | Rear panel I/O ports | |
|--|---|---|--|
| Processor manufacturer * Processor socket * | Intel LGA 1700 | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * | 2 |
| | Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5. Intel® Core™ i7. | USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity * | 1 |
| Compatible processor series * | Intel® Core™ i9, Intel® Pentium® Gold | USB 3.2 Gen 2x2 Type-C ports quantity | 1 |
| Supported processor sockets | LGA 1700 | Ethernet LAN (RJ-45) ports * | 1 |
| Memory Supported memory types * DDR4-SDRAM | | PS/2 ports quantity | 1 |
| Number of memory slots * 4 Memory slots type DIMM | | HDMI ports quantity * | 1 |
| Memory channels Dual-channel Non-ECC V 3133 2400 2565 3900 3300 3300 3300 3303 3400 | 10,3466,3600,3733,3866,4000,4133,4266,4400,4500,4600,4700,4800,5000,5066,5133,533 | DisplayPorts quantity | 1 |
| Supported memory clock speed MHz Supported memory clock speed | U,3400,30UU,3733,3800,4UUU,4133,4200,44UU,43UU,49UU,47UU,40UU,3UUU,3UG0,3133,333 | Headphone outputs | 1 |
| (max) Maximum internal memory * 128 GB Unbuffered memory * / | | Line-in | ✓ |
| Storage controllers | | Microphone in | ✓ |
| Supported storage drive types | HDD & SSD | Network | |
| Supported storage drive interfaces | | Ethernet LAN | 1 |
| RAID support | ✓ | Ethernet interface type | 2.5 Gigabit Ethernet |
| RAID levels | 0, 1, 5, 10 | Wi-Fi * | ✓ |
| Graphics | 0, 1, 3, 10 | Top Wi-Fi standard | Wi-Fi 6 (802.11ax) |
| Parallel processing technology support * | Not supported | Wi-Fi standards | 802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax) |
| Internal I/O | | Bluetooth | ✓ |
| USB 2.0 connectors * | 2 | Bluetooth version | 5.2 |
| USB 3.2 Gen 1 (3.1 Gen 1) connectors * | 2 | Features | |
| USB 3.2 Gen 2 (3.1 Gen 2) | | Motherboard chipset * | Intel Z790 |
| connectors * | 1 | Audio output channels * | 7.1 channels |
| Number of SATA III connectors * | 4 | Component for * | PC |
| S/PDIF out connector | ✓ | Motherboard form factor * | ATX |
| Front panel audio connector | ✓ | Motherboard chipset family * | Intel |
| ATX Power connector (24-pin) | ✓ | Power source type | ATX |
| CPU fan connector | ✓ | Windows operating systems supported | Windows 10 x64, Windows 11 |
| Number of chassis fan connectors | 3 | | |

| Internal I/O | | Expansion slots | |
|--|------------|---|--------------------------------------|
| Peripheral (Molex) power connectors (4-pin) EPS power connector (8-pin) Number of COM connectors TPM connector Thunderbolt headers 1 12V power connector RGB LED pin header | 1 1 1 1 | PCI Express x1 (Gen 3.x) slots PCI Express x16 (Gen 4.x) slots PCI Express x16 (Gen 5.x) slots Number of M.2 (M) slots BIOS | 1 3 1 3 |
| | √ ✓ | BIOS type * BIOS memory size Clear CMOS button | UEFI AMI 192 Mbit ✓ |
| Rear panel I/O ports | | Packaging data | • |
| USB 2.0 ports quantity * | 4 | Package width Package depth Package height Package weight | 338 mm 273 mm 68 mm 1.68 kg |
| | | Weight & dimensions | |
| | | Width Depth | 305 mm 234 mm |
| | | Packaging content | |
| | | Cables included | SATA |





4711081944843

0195553944847



195553944847

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.