



# Biamp Desono P30DT Two-Way 4.25-inch Pendant Mount Loudspeaker Black

**Brand :** Biamp                      **Product family:** Desono                      **Product code:** 911.0905.900

**Product name :** P30DT Two-Way 4.25-inch Pendant Mount Loudspeaker Black



P30DT Two-Way 4.25-inch Pendant Mount Loudspeaker Black

Biamp Desono P30DT Two-Way 4.25-inch Pendant Mount Loudspeaker Black:

The P30DT two-way, 4.25" pendant loudspeaker brings exceptional dispersion to areas with open ceilings, while offering clear speech and musical purity. Available in black or white, the P30DT is suitable for a wide range of background and foreground audio applications.

The Gripple cable fasteners, Euroblock connector, and 70V/100V tap switch can be hidden after installation by the innovatively designed end cap. The attractive aesthetics and ease-of-installation make this product an industry standard.

Certified for use with Zoom software.  
Biamp Desono P30DT Two-Way 4.25-inch Pendant Mount Loudspeaker Black. Recommended usage: Universal. Speaker type: 2-way. Connectivity technology: Wired. RMS rated power: 50 W, Frequency range: 75 - 20000 Hz, Impedance: 16  $\Omega$ , Sensitivity: 84 dB. Product colour: Black

Loudspeakers		Amplifier	
Speaker type *	2-way	Amplifier *	✗
Speaker placement *	Pendant-mountable	Recommended amplifier power (max)	100 W
Tweeter	✓	Recommended amplifier power (min)	50 W
Number of tweeter drivers	1	Ports & interfaces	
Tweeter diameter	2.5 cm	Connectivity technology *	Wired
Tweeter diameter (imperial)	2.54 cm (1")	Bluetooth *	✗
Woofer	✓	Weight & dimensions	
Number of woofer drivers	1	Height	223 mm
Woofer diameter	10.8 cm	Weight	2.6 kg
Woofer diameter (imperial)	10.8 cm (4.25")	Diameter	23.3 cm
Audio		Packaging data	
RMS rated power *	50 W	Package width	293.9 mm
Peak Music Power Output (PMPO)	200 W	Package depth	305.1 mm
Frequency range	75 - 20000 Hz	Package height	313.9 mm
Impedance	16 $\Omega$	Package weight	3.55 kg
Sensitivity	84 dB	Packaging content	
Sound pressure level (max)	110 dB	Mounting brackets included	✓
Input sensitivity	2830 mV	Logistics data	
Performance		Export Control Classification Number (ECCN)	EAR99
Recommended usage *	Universal	Harmonized System (HS) code	8518220000
Product colour *	Black	Other features	
Suitable for outdoor use	✗	Country of origin	China



5420035220597



0810039100400



810039100400

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 29-OCT-2024. Prints or copies of Information are only valid on the printed Publication date