

POLY Trio 8800 IP Conference Phone and PoE-enabled

Brand: POLY Product code: 849A7AA

Product name : Trio 8800 IP Conference Phone and PoEenabled

- Catch every word and enjoy inflection without distracting background noise with Poly Acoustic Clarity technology.
- Collaborate using audio, video, content, or all three. The Trio 8800 conference phone helps teams make decisions faster thanks to their choice of meeting preferences.
- Connect to the platform you like best or choose more than one with Poly hybrid registration. Trio $8800\ \text{IP}$ Conference Phone and PoE-enabled



Big room. Vast possibilities

Transform your large meeting rooms into havens of productive collaboration. With up to 20 ft/6 m of pickup range, quality audio, and Poly NoiseBlockAl technology, you can ensure the flow of ideas is uninterrupted.

POLY Trio 8800 IP Conference Phone and PoE-enabled. Product type: IP conference phone, Product colour: Black, Display diagonal: 12.7 cm (5"). USB connector type: Micro-USB B, USB Type-A. Sustainability certificates: ENERGY STAR. Width: 383 mm, Depth: 75 mm, Height: 332 mm. Cables included: LAN (RJ-45), USB







Features		Ports & interfaces	
Product type * Product colour	IP conference phone Black	USB connector type USB ports quantity	Micro-USB B, USB Type-A 2
Built-in display *	✓	Sustainability	
Display diagonal	12.7 cm (5")	Sustainability certificates	ENERGY STAR
Display resolution	720 x 1280 pixels	Operational conditions	
Voice codecs Number of microphone arrays	G.711alaw, G.711ulaw, G.719, G.722, G.722.1, G.722.1C, G.729ab, OPUS, iLBC 3	Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -20 - 70 °C
Wi-Fi	✓	Operating relative humidity (H-H)	5 - 95%
Top Wi-Fi standard	Wi-Fi 4 (802.11n)	Weight & dimensions	
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n)	Width Depth	383 mm 75 mm
Bluetooth	✓	Height	332 mm
Bluetooth version	4.2	Weight	950 g
Ethernet interface type	Gigabit Ethernet	Package width	483 mm
Ethernet LAN data rates	10,100,1000 Mbit/s	Package depth	115 mm
Networking standards	IEEE 802.3af, IEEE 802.3at	Package height	394 mm
Power over Ethernet (PoE)	✓	Package weight	2.2 kg
Built-in speaker(s) *	√	Packaging content	
Number of speakers	1	Cables included	LAN (RJ-45), USB
Ports & interfaces			LAN (19-45), 000
RJ-45 ports quantity	2	Logistics data	
USB port	✓	Country of origin	Laos, Mexico
USB version	2.0		













Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.