

## POLY VVX 250 4-Line IP Phone and PoE-enabled

Product code: 89B62AA **Brand:** POLY

Product name: VVX 250 4-Line IP Phone and PoE-

enabled

- Hear every nuance on the Poly VVX 250 IP desk phone with quality audio featuring Poly HD Voice. And reduce distracting background noise at the source with Poly Acoustic Fence technology.
- Your phones stay cleaner for longer with integrated Microban® antimicrobial product protection [1] actively reducing the growth of bacteria 24/7. VVX 250 4-Line IP Phone and PoE-enabled

## POLY VVX 250 4-Line IP Phone and PoE-enabled:

## For today's office

Quality sound is standard on the Poly VVX 250 IP desk phone. You'll appreciate all the smart features on non-stop call days, but equally love the color display. It's a win-win for today's office environments.







Design		Network	
Product type * Handset type Product colour *	IP Phone Wired handset Black	Ethernet LAN data rates Security algorithms Syslog	10,100,1000 Mbit/s 802.1x RADIUS, HTTPS ✓
Phone features		Technical details	
Lines quantity *	4 lines	Warranty period	1 year(s)
Call waiting		Ports & interfaces	
Distinctive ring Speed dialling Call hold Call forwarding		USB 2.0 ports quantity Ethernet LAN (RJ-45) ports	1 2
		Certificates	
Conference call	✓	Sustainability certificates	ENERGY STAR
Redialing Do not disturb function Call transfer	<b>4 4 4</b>	Safety	UL 60950-1/62368-1, CE Mark, CAN/CSA C22.2 No 60950-1/62368-1-1, EN 60950-1/62368-1, IEC 60950-1/62368-1, AS/NZS 60950-1
Display Display diagonal Display resolution Touchscreen *	LED 7.11 cm (2.8") 320 x 240 pixels	Certification	FCC Part 15 (CFR 47) Class B ICES-003 Class B EN55032 Class B CISPR32 Class B VCCI Class B EN55024 EN61000-3-2; EN61000-3-3 NZ Telepermit Korea KCC3 UAE TRA Russia CU3 Brazil ANATEL3 Australia RCM South Africa
Speakerphone *	1		ICASA3 Saudi Arabia CITC China CCC3 RoHS Complian TAA
Voice codecs	G.711, G.722, G.722.1, G.729ab, OPUS, iLBC	Power	2222 30p.i.a
Voice activity detection	✓	Power over Ethernet (PoE) *	<b>√</b>
Comfort noise generation (CNG)	✓	AC adapter output voltage	5 V 3 A
Network		AC adapter output current	2 W
Ethernet LAN *	✓		

Network		Operational conditions	
Ethernet LAN interface type	Gigabit Ethernet	Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 5 - 95%
		Storage temperature (T-T)	-40 - 70 °C
		Packaging content	
		Number of handles included *	1 pc(s)
		AC adapter included	✓









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.