POLY Trio C60 IP Conference Phone for Microsoft Teams and PoE-enabled No Radio

Brand : POLY

Product code: 830A1AA

Product name : Trio C60 IP Conference Phone for Microsoft Teams and PoE-enabled No Radio

- Get more out of your conference calls. Poly reduces distracting background noise to ensure every inflection is heard. Hear every reaction with up to 22 kHz of rich, full sound.
- All it takes is a fingertip to get started. Join your calls in a second with a single touch of a button thanks to the truly intuitive user experience.
Trio C60 IP Conference Phone for Microsoft Teams and PoE-enabled No Radio

POLY Trio C60 IP Conference Phone for Microsoft Teams and PoE-enabled No Radio:

One device. Many possibilities.
Bring people together. Launch big ideas. And make sure everyone at the table can be heard, near or far with Poly signature audio. The Trio C60 plays nicely with everyone, delivering native experiences on your favorite collaboration platforms.
POLY Trio C60 IP Conference Phone for Microsoft Teams and PoE-enabled No Radio. Product type: IP conference phone, Product colour: Black, Display type: LCD. USB connector type: Micro-USB B, USB Type-A. Sustainability certificates: ENERGY STAR. Width: 383 mm, Depth: 75 mm, Height: 332 mm. Cables included: LAN (RJ-45), USB

Features

Product type *	IP conference phone
Product colour	Black
Built-in display *	✓
Display type	LCD
Display diagonal	12.7 cm (5")
Display resolution	720 x 1280 pixels
Touchscreen	✓
Voice codecs	G.711a, G.711u, G.719, G.722, G.722.1, G.722.1C, G.729ab, OPUS, iLBC
Wi-Fi	✓
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n)
Bluetooth	✓
Bluetooth version	4.2
Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Power over Ethernet (PoE)	✓
Security algorithms	EAP-TLS, FIPS 140-2, MSCHAPv2, PEAP, TLS, WEP, WPA, WPA2, WPA2-Enterprise
Built-in speaker(s) *	✓

Ports & interfaces

RJ-45 ports quantity	2
USB port	✓

Ports & interfaces

USB version	2.0
USB connector type	Micro-USB B, USB Type-A
USB ports quantity	2

Sustainability

Sustainability certificates	ENERGY STAR

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 70 °C
Operating relative humidity (H-H)	5 - 95%

Weight & dimensions

Width	383 mm
Depth	75 mm
Height	332 mm
Weight	950 g
Package width	483 mm
Package depth	115 mm
Package height	394 mm
Package weight	1.97 kg

Packaging content

Cables included	LAN (RJ-45), USB

0197497342963

197497342963