



## POLY Trio C60 IP Conference Phone and PoE-enabled No Radio

**Brand :** POLY

**Product code:** 830A2AA

**Product name :** Trio C60 IP Conference Phone and PoE-enabled No Radio

- Get more out of your conference calls. Poly reduces distracting background noise to ensure every inflection is heard. Hear every reaction with up to 22 kHz of rich, full sound.
  - All it takes is a fingertip to get started. Join your calls in a second with a single touch of a button thanks to the truly intuitive user experience.
- Trio C60 IP Conference Phone and PoE-enabled No Radio



[POLY Trio C60 IP Conference Phone and PoE-enabled No Radio:](#)



One device. Many possibilities.


Bring people together. Launch big ideas. And make sure everyone at the table can be heard, near or far with Poly signature audio. The Trio C60 plays nicely with everyone, delivering native experiences on your favorite collaboration platforms.

POLY Trio C60 IP Conference Phone and PoE-enabled No Radio. Product type: IP conference phone, Product colour: Black, Display type: LCD. USB connector type: Micro-USB B, USB Type-A. Sustainability certificates: ENERGY STAR. Width: 383 mm, Depth: 75 mm, Height: 332 mm. Cables included: LAN (RJ-45), USB

Features		Ports & interfaces	
Product type *	IP conference phone	USB ports quantity	2
Product colour	Black	Sustainability	
Built-in display *	✓	Sustainability certificates	ENERGY STAR
Display type	LCD	Operational conditions	
Display diagonal	12.7 cm (5")	Operating temperature (T-T)	0 - 40 °C
Display resolution	720 x 1280 pixels	Storage temperature (T-T)	-20 - 70 °C
Touchscreen	✓	Operating relative humidity (H-H)	5 - 95%
Voice codecs	G.722, G.722.1, G.722.1C, G.729ab, G.711a, G.711u, iLBC, G.719, OPUS	Weight & dimensions	
Ethernet interface type	Gigabit Ethernet	Width	383 mm
Ethernet LAN data rates	10,1000,100 Mbit/s	Depth	75 mm
Power over Ethernet (PoE)	✓	Height	332 mm
Security algorithms	WPA2-Enterprise, MSCHAPv2, TLS, PEAP, WEP, WPA, EAP-TLS, FIPS 140-2, WPA2	Weight	950 g
Built-in speaker(s) *	✓	Package width	483 mm
Ports & interfaces		Package depth	115 mm
RJ-45 ports quantity	2	Package height	394 mm
USB port	✓	Package weight	1.97 kg
USB version	2.0	Packaging content	
USB connector type	Micro-USB B, USB Type-A	Cables included	LAN (RJ-45), USB



0197497342970



197497342970

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.