



## POLY CCX 400 Business Media Phone with Open SIP and PoE-enabled

**Brand :** POLY

**Product code:** 849A1AA

**Product name :** CCX 400 Business Media Phone with Open SIP and PoE-enabled

- Hear every nuance with Poly HD Voice and Poly Acoustic Clarity technologies. Poly Acoustic Fence technology reduces distracting background noise and makes calling a pleasure.
- Enjoy the ergonomic design and the intuitive user touchscreen interface that saves you the hassle of learning new features and functions. When a phone is this easy, better collaboration and productivity aren't far behind.

CCX 400 Business Media Phone with Open SIP and PoE-enabled

[POLY CCX 400 Business Media Phone with Open SIP and PoE-enabled:](#)

"Entry-level" just got sweeter


The Poly CCX 400 is an entry-level business phone that's easy to use. Its interface is simple and intuitive. And contacts and meetings are one swipe or one tap away on a color touch screen.



<b>Design</b>		<b>Ports &amp; interfaces</b>	
Product type *	IP Phone	USB 2.0 ports quantity	1
Handset type	Wired handset	Ethernet LAN (RJ-45) ports	2
Product colour *	Black	RJ-9 ports quantity	1
<b>Phone features</b>		<b>Power</b>	
Lines quantity *	24 lines	Power over Ethernet (PoE) *	✓
Caller ID *	✓	<b>Operational conditions</b>	
<b>Display</b>		Operating temperature (T-T)	0 - 40 °C
Display	LCD	Operating relative humidity (H-H)	5 - 95%
Display diagonal	12.7 cm (5")	Storage temperature (T-T)	-40 - 70 °C
Display resolution	720 x 1280 pixels	<b>Weight &amp; dimensions</b>	
Aspect ratio	16:9	Package width	222 mm
Touchscreen *	✓	Package depth	243 mm
<b>Audio</b>		Package height	69 mm
Speakerphone *	✓	Package weight	1 kg
Voice codecs	G.722, G.729ab, G.711alaw, iLBC, G.711ulaw, OPUS	<b>Packaging content</b>	
<b>Network</b>		Handset	✓
Ethernet LAN *	✓	Number of handles included *	1 pc(s)
Ethernet LAN interface type	Gigabit Ethernet	Cables included	LAN (RJ-45)
Ethernet LAN data rates	10,100,1000 Mbit/s	Stand included	✓
Wi-Fi *	✗	<b>Logistics data</b>	
Bluetooth *	✗	Country of origin	China
Security algorithms	256-bit AES, SRTP, TLS		



0197497506297



197497506297



0197497506280



197497506280

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.