



# DELL P5524QT Interactive flat panel 139.7 cm (55") LCD 350 cd/m<sup>2</sup> 4K Ultra HD Black Touchscreen

Brand : DELL

Product code: DELL-P5524QT

Product name : P5524QT



- 54.64" 4K UHD 3840 x 2160, IPS
- 8ms, 16:9, 350cd/m<sup>2</sup>, 1200:1
- USB, HDMI, DisplayPort"
- 54.64" 4K UHD 3840 x 2160, IPS, 16:9, 350 cd/m<sup>2</sup> 1.07 Billion, 8 ms, 178°/178°, 1200:1

DELL P5524QT Interactive flat panel 139.7 cm (55") LCD 350 cd/m<sup>2</sup> 4K Ultra HD Black Touchscreen:



Bring the team together, whether they are in the room or remote, with this brilliant 55" 4K UHD large format monitor with 20-point touch, palm-rejection, USB-C connectivity and built-in dual 10W speakers. DELL P5524QT. Product design: Interactive flat panel. Display diagonal: 139.7 cm (55"), Display technology: LCD, Display resolution: 3840 x 2160 pixels, Display brightness: 350 cd/m<sup>2</sup>, HD type: 4K Ultra HD, Touchscreen. Product colour: Black

Display		Design	
Panel type	IPS	Bezel width (top)	4.47 cm
LED backlight	✓	Anti-glare screen	✓
Display diagonal *	139.7 cm (55")	<b>Performance</b>	
Display technology *	LCD	Purpose *	Corporate
Display resolution *	3840 x 2160 pixels	On Screen Display (OSD)	✓
Display brightness *	350 cd/m <sup>2</sup>	<b>Power</b>	
HD type *	4K Ultra HD	Power consumption (typical) *	77.1 W
Touchscreen *	✓	Power consumption (standby) *	0.5 W
Number of simultaneous touchpoints	20	Power consumption (off)	0.3 W
Multi-touch	✓	Power consumption (max)	320 W
Native aspect ratio	16:9	Energy efficiency class (SDR)	F
Contrast ratio (typical)	1300:1	Energy efficiency class (HDR)	Not available
Viewing angle, horizontal	178°	Energy consumption (SDR) per 1000 hours	77 kWh
Viewing angle, vertical	178°	AC input voltage	100 - 240 V
Display number of colours	1.07 billion colours	AC input frequency	50/60 Hz
Pixel pitch	0.315 x 0.315 mm	Heat dissipation	263.08 BTU/h
Display diagonal (metric)	138.787 cm	Energy efficiency scale	A to G
Horizontal scan range	30 - 140 kHz	<b>Computer system</b>	
Vertical scan range	24 - 75 Hz	Windows operating systems supported	Windows 7 Professional, Windows 7 Ultimate, Windows 8, Windows 8.1
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200, 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160	Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan
Supported video modes	480p, 576p, 720p, 1080i, 1080p, 2160p	Linux operating systems supported	✓
Hardness	3H	<b>Weight &amp; dimensions</b>	
Native refresh rate	60 Hz	Display width	1299 mm
RGB colour space	NTSC	Display depth	78.7 mm
Colour gamut	72%	Display height	769.8 mm
<b>Ports &amp; interfaces</b>		Display weight	34.3 kg
HDMI ports quantity *	3	<b>Packaging data</b>	
HDMI version	2.0	Package weight	41.9 kg
DVI port *	✗	<b>Packaging content</b>	
DisplayPorts quantity *	1	Remote control included	✓
USB port *	✓	Stylus pen	✓
USB ports quantity	8	Number of stylus pens	2
USB version	2.0/3.2 Gen 1 (3.1 Gen 1)	Cables included	DisplayPort, HDMI, USB, USB Type-C

Ports & interfaces		Operational conditions	
USB connector type	USB Type-A	Operating temperature (T-T)	0 - 40 °C
USB 2.0 Type-B ports quantity	3	Operating relative humidity (H-H)	10 - 80%
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4	Storage temperature (T-T)	-20 - 60 °C
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1	Storage relative humidity (H-H)	5 - 90%
USB Power Delivery	✓	Operating altitude	0 - 5000 m
USB Power Delivery up to	90 W	Non-operating altitude	0 - 12192 m
USB Type-C DisplayPort Alternate Mode	✓	<b>Features</b>	
Ethernet LAN *	✓	Heat dissipation (max)	1091.89 BTU/h
Ethernet LAN (RJ-45) ports	1	<b>Technical details</b>	
Wi-Fi *	✗	Sustainability compliance	✓
Audio (L/R) in	1	Sustainability certificates	ENERGY STAR
RS-232 interface	✓	Doesn't contain	Arsenic, Mercury, PVC/BFR
<b>Audio</b>		Compliance certificates	RoHS
Built-in speaker(s) *	✓	<b>Other features</b>	
Number of built-in speakers	2	Quick start guide	✓
RMS rated power	20 W	Cable lock slot	✓
Speaker impedance	8 Ω	LED indicators	✓
Speaker frequency range	120 - 20000 Hz	On/off switch	✓
<b>Design</b>		Viewable size, horizontal	121 cm
Product design *	Interactive flat panel	Viewable size, vertical	68 cm
Placement supported *	Indoor	Power supply type	Internal
Product colour *	Black	Cable management	✓
Screen shape	Flat	Response time	9 s
VESA mounting *	✓	Plug and Play	✓
Panel mounting interface	300 x 400 mm		
Bezel width (bottom)	4.47 cm		
Bezel width (side)	4.47 cm		



5397184821534

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 29-OCT-2024. Prints or copies of Information are only valid on the printed Publication date