

ASUS TUF Gaming TUF-RTX4070TIS-016G-GAMING NVIDIA GEForce RTX 4070 Ti SUPER 16 GB GDDR6X

Product family: TUF Gaming Product code: 90YV0KF0-

M0NA00

298

Product name: TUF-RTX4070TIS-O16G-GAMING

Brand: ASUS

- Powered by NVIDIA DLSS3, ultra-efficient Ada Lovelace arch, and full ray tracing
- 4th Generation Tensor Cores: Up to 4x performance with DLSS 3 vs. brute-force rendering
- 3rd Generation RT Cores: Up to 2X ray tracing performance
- OC mode: 2670 MHz (OC mode)/ 2640 MHz (Default mode)
- Axial-tech fans scaled up for 21% more airflow
- Dual ball fan bearings last up to twice as long as conventional designs
- Military-grade capacitors rated for 20K hours at 105C make the GPU power rail more durable
- Metal exoskeleton adds structural rigidity and vents to increase heat reliability
- Auto-Extreme precision automated manufacturing for higher reliability
- GPU Tweak III software provides intuitive performance tweaking, thermal controls, and system monitoring

TUF Gaming GeForce RTX 4070 Ti SUPER 16GB GDDR6X OC Edition with DLSS 3, lower temps, and enhanced durability



Processor		Performance	
CUDA * CUDA cores Graphics processor family * Graphics processor * Processor boost clock speed Processor frequency (OC mode) Maximum resolution * Parallel processing technology	8448 NVIDIA GeForce RTX 4070 Ti SUPER 2640 MHz 2670 MHz 7680 x 4320 pixels Not supported	TV tuner integrated * DirectX version * OpenGL version * HDCP HDCP version Dual Link DVI * NVIDIA G-SYNC NVIDIA Ansel	X 12 Ultimate 4.6 ✓ 2.3 X ✓
support * Maximum displays per videocard	4	Design Cooling type *	Active
Memory Discrete graphics card memory * Graphics card memory type * Memory bus * Data transfer rate Ports & interfaces	16 GB GDDR6X 256 bit 21 Gbit/s	Number of fans Form factor Number of slots Illumination Illumination colour Product colour	3 fan(s) Full-Height/Full-Length (FH/FL) 3.25 ✓ Multi Black
Interface type * HDMI ports quantity * HDMI version DisplayPorts quantity * DisplayPort version	PCI Express 4.0 2 2.1a 3 1.4a	Power Minimum system power supply * Supplementary power connectors Weight & dimensions Length Depth Height	750 W 1x 16-pin 305 mm 65 mm 138 mm
		Packaging data Package type	



4711387437834

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.