



Vertiv GXT5-1500IRT2UXL uninterruptible power supply (UPS) Double-conversion (Online) 1.5 kVA 1500 W



Brand : Vertiv

Product code: GXT5-1500IRT2UXL


Product name : GXT5-1500IRT2UXL

- Top-level on-line double conversion UPS for mission-critical applications
- Unity output power factor
- LCD multi-language color display (gravity sensing)
- On-line (VFI) mode efficiency up to 94% at full load
- Active ECO mode efficiency up to 98%
- Energy Star 2.0 certified
- Controllable and programmable output sockets


1500 VA / 1500 W, in 230 VAC, 50 Hz / 60 Hz, out 200/208/220/230/240 VAC, Sine wave, 93% Efficiency, 4 x 12 V x 9.0 Ah

Vertiv GXT5-1500IRT2UXL. UPS topology: Double-conversion (Online), Output power capacity: 1.5 kVA, Output power: 1500 W. Power plug: C14 coupler, Serial interface type: RJ-45. Battery capacity: 9 Ah, Battery voltage: 12 V, Charging current: 2.2 A. Form factor: Tower, Product colour: Black, Rack capacity: 2U. Width: 430 mm, Depth: 470 mm, Height: 85 mm

Features		Battery	
UPS topology *	Double-conversion (Online)	Battery capacity	9 Ah
Output power capacity *	1.5 kVA	Battery voltage	12 V
Output power *	1500 W	Number of batteries supported	4
Waveform *	Pure sine	Charging current	2.2 A
Input operation voltage (min) *	230 V	Design	
Input operation voltage (max) *	230 V	Form factor *	Tower
Input frequency *	40 - 70 Hz	Rack capacity	2U
Output operation voltage (min)	200 V	Product colour *	Black
Output operation voltage (max)	240 V	Display type	LCD
Efficiency	93%	Certification	UL-1778 (Fifth Edition), C-UL listed, IEC 62040-1: 2008 (First Edition) + Am 1:2013, EN 62040-1:2008+A1:2013, CISPR22 Class A (RFI)/ FCC Part 15 (Class A), ISTA Procedure 1A, ANSI C62.41 Category B
Power factor	0.99		
ECO mode	✓	Operational conditions	
Noise level	46 dB	Operating temperature (T-T)	0 - 40 °C
Ports & interfaces		Storage temperature (T-T)	-20 - 60 °C
Power plug	C14 coupler	Operating relative humidity (H-H)	0 - 95%
USB port	✓	Operating altitude	0 - 3000 m
Serial interface	✓	Weight & dimensions	
Serial interface type	RJ-45	Width	430 mm
Modem (RJ-11) ports	1	Depth	470 mm
Ethernet LAN (RJ-45) ports	2	Height	85 mm
		Weight	21 kg



0767041026528



767041026528

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.