



DELL UltraSharp 30 USB-C Hub Monitor - U3023E

Brand : DELL

Product family: UltraSharp

Product code: DELL-U3023E

Product name : Dell UltraSharp
30 USB-C Hub Monitor - U3023E

- 76.2cm (30") WQXGA 2560 x 1600 LED IPS
- 8ms, 16:10, 350cd/m², 1000:1
- USB, HDMI, DisplayPort
76.2cm (30") WQXGA 2560 x 1600 LED IPS, 16:10, 350cd/m², 1.07B, 8ms, 178°/178°, 1000:1

DELL UltraSharp 30 USB-C Hub Monitor - U3023E:

Make more possible with this 30" 16:10 monitor with wide color coverage, multitasking features and a host of connectivity ports.

DELL UltraSharp 30 USB-C Hub Monitor - U3023E. Display diagonal: 76.2 cm (30"), Display resolution: 2560 x 1600 pixels, HD type: WQXGA, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:10, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 3.2 Gen 2 (3.1 Gen 2). VESA mounting, Height adjustment. Product colour: Silver



Display		Ergonomics	
Display diagonal *	76.2 cm (30")	Tilt adjustment	✓
Display resolution *	2560 x 1600 pixels	Tilt angle range	-5 - 21°
HD type *	WQXGA	On Screen Display (OSD)	✓
Native aspect ratio *	16:10	Plug and Play	✓
Display technology *	LCD	Power	
Panel type *	IPS	Energy efficiency class (SDR) *	F
Backlight type	LED	Energy efficiency class (HDR) *	Not available
Touchscreen *	✗	Energy consumption (SDR) per 1000 hours *	27 kWh
Display brightness (typical)	350 cd/m ²	Power consumption (typical) *	26.6 W
Response time *	8 ms	Power consumption (standby) *	0.3 W
Anti-glare screen	✓	Power consumption (max)	210 W
Screen shape *	Flat	Power consumption (off)	0.2 W
Supported video modes	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	AC input voltage	100 - 240 V
Contrast ratio (typical) *	1000:1	AC input frequency	50 - 60 Hz
Maximum refresh rate *	60 Hz	Power supply type	Internal
Viewing angle, horizontal	178°	Energy efficiency scale	A to G
Viewing angle, vertical	178°	European Product Registry for Energy Labelling (EPREL) code	928122
Display number of colours *	1.07 billion colours	Operational conditions	
Response time (fast)	5 ms	Operating temperature (T-T)	0 - 40 °C
Pixel pitch	0.2505 x 0.2505 mm	Storage temperature (T-T)	-20 - 60 °C
Pixel density	101.4 ppi	Operating relative humidity (H-H)	10 - 80%
Horizontal scan range	30 - 113 kHz	Storage relative humidity (H-H)	5 - 90%
Vertical scan range	56 - 76 Hz	Operating altitude	0 - 5000 m
Viewable size, horizontal	64.1 cm	Non-operating altitude	0 - 12192 m
Viewable size, vertical	40.1 cm	Weight & dimensions	
Display diagonal (metric)	75.62 cm	Width (with stand)	655.9 mm
High Dynamic Range (HDR) supported	✗	Depth (with stand)	230 mm
DDC/CI	✓		
Surface hardness	3H		

Display		Weight & dimensions	
Colour gamut standard	sRGB	Height (with stand)	472.7 mm
sRGB coverage (typical)	100%	Weight (with stand)	10.8 kg
DCI-P3 coverage	95%	Width (without stand)	655.9 mm
Heat dissipation (typical)	90.76 BTU/h	Depth (without stand)	53 mm
Performance		Height (without stand)	418.6 mm
NVIDIA G-SYNC *	✗	Weight (without stand)	6.48 kg
AMD FreeSync *	✗	Bezel width (side)	7.3 mm
Flicker-free technology	✓	Bezel width (top)	7.3 mm
Low Blue Light technology	✓	Bezel width (bottom)	1.05 cm
Multimedia		Packaging data	
Built-in speaker(s) *	✗	Package weight	15.1 kg
Built-in camera *	✗	Packaging content	
Design		Stand included	✓
Market positioning *	Graphics design	Cables included	AC, DisplayPort, USB Type-C, USB Type-C to USB Type-A
Product colour *	Silver	Quick start guide	✓
Front bezel colour	Black	Sustainability	
Feet colour	Silver	Sustainability certificates	ENERGY STAR, EPEAT Gold
Ports & interfaces		Doesn't contain	Arsenic, PVC/BFR
Built-in USB hub *	✓	Carbon footprint	
USB hub version	3.2 Gen 2 (3.1 Gen 2)	Total carbon footprint (kg of CO2e)	820
USB upstream port type	USB Type-C	Total carbon emissions, standard deviation (kg of CO2e)	177
Number of upstream ports	2	Carbon emissions, manufacturing (kg of CO2e)	419
USB Type-A downstream ports quantity	4	Carbon emissions, logistics (kg of CO2e)	137
USB Type-C downstream ports quantity	1	Carbon emissions, energy usage (kg of CO2e)	255
USB Power Delivery	✓	Carbon emissions, end-of-life (kg of CO2e)	9
USB Power Delivery up to	90 W	Total carbon emissions, w/o use phase (kg of CO2e)	565
HDMI *	✓	PAIA version	1.3.0
HDMI ports quantity	1	Other features	
HDMI version	1.4	On/off switch	✓
DisplayPorts quantity	2	Picture-by-Picture (PbP)	✓
Audio output	✓	Maximum resolution	2560 x 1600 pixels
Headphone out *	✓	RJ-45 ports quantity	1
Headphone outputs	1	Heavy metals free	Hg (mercury)
Headphone connectivity	3.5 mm	Compliance certificates	RoHS
HDCP	✓	Power management	✓
Charging port type	USB Type-C + USB Type-A	ENERGY STAR certified Monitor. EPEAT registered where applicable. TCO Certified & TCO Certified Edge. RoHS Compliant. BFR/PVC Free monitor Meets NFPA 99 leakage current requirements. Arsenic-Free glass and Mercury-Free for the panel only.	
AC (power) in	✓	Logistics data	
Network		Harmonized System (HS) code	85285210
Wi-Fi	✗	Compliance industry standards	
Ergonomics		ENERGY STAR certified Monitor. EPEAT registered where applicable. TCO Certified & TCO Certified Edge. RoHS Compliant. BFR/PVC Free monitor Meets NFPA 99 leakage current requirements. Arsenic-Free glass and Mercury-Free for the panel only.	
VESA mounting *	✓	Logistics data	
Panel mounting interface	100 x 100 mm	Harmonized System (HS) code	85285210
Cable lock slot *	✓	Compliance industry standards	
Height adjustment *	✓	ENERGY STAR certified Monitor. EPEAT registered where applicable. TCO Certified & TCO Certified Edge. RoHS Compliant. BFR/PVC Free monitor Meets NFPA 99 leakage current requirements. Arsenic-Free glass and Mercury-Free for the panel only.	
Height adjustment	15 cm	Logistics data	
Pivot	✓	Harmonized System (HS) code	85285210
Pivot angle	-90 - 90°	Compliance industry standards	
Swivelling	✓	ENERGY STAR certified Monitor. EPEAT registered where applicable. TCO Certified & TCO Certified Edge. RoHS Compliant. BFR/PVC Free monitor Meets NFPA 99 leakage current requirements. Arsenic-Free glass and Mercury-Free for the panel only.	
Swivel angle range	-30 - 30°	Logistics data	



5397184567593



0884116398868



884116398868



5715063472811

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.