



Linksys Hydra Pro 6E wireless router Gigabit Ethernet Tri-band (2.4 GHz / 5 GHz / 5 GHz) Black

Brand : Linksys

Product code: MR7500-UK

Product name : Hydra Pro 6E

- The new 6 GHz band offers interference-free signal and ultra-fast speeds
- Unleash multi-gig speed for livestreaming, VR gaming, video conferencing
- Ultra-fast data streaming and connection between devices
- Extreme speeds and limitless connectivity throughout your home
- Coverage up to 2700 sq. ft., 55+ devices, and speed up to 6.6 Gbps

Hydra Pro 6E MR7500 - Tri-Band AXE6600 Mesh WiFi 6E Router

Linksys Hydra Pro 6E. WAN connection type: RJ-45. Wi-Fi band: Tri-band (2.4 GHz / 5 GHz / 5 GHz), Top Wi-Fi standard: Wi-Fi 6 (802.11ax), WLAN data transfer rate (max): 6600 Mbit/s. Ethernet LAN interface type: Gigabit Ethernet, Ethernet LAN data rates: 10,100,1000 Mbit/s, Cabling technology: 10/100/1000Base-T(X). Number of data streams: 4x4. Security algorithms: 128-bit WEP, WPA2, WPA3



WAN connection		Management features	
Ethernet WAN *	✓	WPS push button	✓
DSL WAN *	✗	Intelligent Mesh technology	✓
SIM card slot *	✗	MU-MIMO technology	✓
3G/4G USB modem compatibility *	✗	MIMO	✓
WAN connection type	RJ-45	Number of data streams	4x4
Wireless LAN features		Security	
Wi-Fi band *	Tri-band (2.4 GHz / 5 GHz / 5 GHz)	Security algorithms	128-bit WEP, WPA2, WPA3
Top Wi-Fi standard *	Wi-Fi 6 (802.11ax)	Design	
WLAN data transfer rate (max) *	6600 Mbit/s	Product colour	Black
Wi-Fi standards	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac), Wi-Fi 6 (802.11ax), Wi-Fi 6E (802.11ax)	Indication light	✓
WLAN data transfer rate (first band)	600 Mbit/s	Product type *	Tabletop router
WLAN data transfer rate (second band)	1200 Mbit/s	Antenna	
WLAN data transfer rate (third band)	4800 Mbit/s	Antenna design *	External
Network		Antennas quantity	4
Ethernet LAN *	✓	Features	
Ethernet LAN interface type *	Gigabit Ethernet	Processor frequency	1800 MHz
Ethernet LAN data rates	10,100,1000 Mbit/s	Processor cores	4
Cabling technology	10/100/1000Base-T(X)	Internal memory	512 MB
Ports & interfaces		Flash memory	512 MB
Ethernet LAN (RJ-45) ports *	4	Power	
USB port *	✓	Power source type *	AC
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	AC input voltage	100 - 240 V
Management features		AC input frequency	50/60 Hz
Reset button	✓	Output voltage	12 V
		Output current	3 A
		Weight & dimensions	
		Width	170 mm
		Depth	280 mm
		Height	60 mm
		Weight	938.9 g

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 29-OCT-2024. Prints or copies of Information are only valid on the printed Publication date