



GIGABYTE UD1000GM PG5 power supply unit 1000 W 20+4 pin ATX ATX Black

Brand : GIGABYTE


Product code: GP-UD1000GM PG5

Product name : UD1000GM PG5

- Main Japanese capacitors
- Enhanced thermal solution
- 120mm smart hydraulic bearing (HYB) fan
- OVP/OPP/SCP/UV/PC/OTP protection
- Support PCIe Gen 5.0 graphics card
- High-quality native 16-pin cable supports 600W output
- 80 PLUS Gold certified
- Fully modular design
- Compact design

1000 W, Fan Size 120 mm, Intel ATX 12 V, 80 PLUS Gold, Black

GIGABYTE UD1000GM PG5. Total power: 1000 W, AC input voltage: 100 - 240 V, AC input frequency: 50 - 60 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 61 cm, SATA power cable length: 150,600 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Width: 150 mm, Depth: 86 mm, Height: 140 mm



Power		Ports & interfaces	
Total power *	1000 W	PCI Express power connectors (16-pin)	1
AC input voltage *	100 - 240 V	PCI Express power cable length	70 cm
AC input frequency	50 - 60 Hz	CPU power connector (4+4 pin)	✓
Input current	6.5 - 15 A	CPU power cable length	80 cm
Power Factor Correction (PFC) type	Active	ATX power connector (20+4 pin)	✓
Hold time	16 ms	Cabling type	Fully-Modular
Efficiency	90%		
Power Good signal delay range	100 - 150 ms		
Power protection features	Over current, Over power, Over voltage, Short circuit, Under voltage		
Ports & interfaces		Performance	
Motherboard power connector *	20+4 pin ATX	80 PLUS certification *	80 PLUS Gold
Motherboard power cable length	61 cm	Purpose *	PC
Number of SATA power connectors	8	Power supply unit (PSU) form factor *	ATX
SATA power cable length	150,600 mm	Bearing technology	HYB
Peripheral (Molex) power connectors (4-pin) *	4	Mean time between failures (MTBF)	100000 h
Peripheral (Molex) power cable length	120,150,500 mm		
PCI Express power connectors (6+2 pin)	4		
		Design	
		Product colour	Black
		Cooling type	Active
		Fan diameter	12 cm
		Weight & dimensions	
		Width	150 mm
		Depth	86 mm
		Height	140 mm



4719331552930



4719331553234

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.