

RTBUS-28XL

Round Table Connection Bus for Power Socket, USB Charging and Cable Pass-Throughs



The RTBUS-28XL is an elegant furniture-mounted, round-connection bus. The RTBUS-28XL features a mechanism for pneumatic lifting and smooth closing of its lid. It is easily installed into a table or podium top. In addition, the unit connects AV equipment to the room's presentation system

TECHNICAL SPECIFICATIONS

Ports USB-C: On a USB-C port (fast charge)

USB Type A: On a USB port (fast charge)

USB Features Rated USB Output: DC 5 V, 4.2 A

Protocol Type-A: QC 3.0

Protocol Type-C: PD 5

Output Power: 30W max

Output Current Voltage Type-A: 5V=3A, 9V=3A, 12V=2.5A, 20V=1.5A

Output Current Voltage Type-C: 5V=3A, 9V=3A, 12V=2.5A, 15V=2A, 20V=1.5A

Output Current Voltage Type-A & Type-C: V=2.4A

Power Socket - Universal: 100-240V AC, 50/60Hz, 5A; maximum 5A per power

outlet

Fuse Rating: T 6.3A 250V

Options: TBUS AC Power Cord (C-AC/POWERCORD) power socket kits

Regulatory Compliance (Standards Compliance) Safety: CE

Environmental: RoHS, WEEE

Environmental Conditions

Operating Temperature: 0° to +40°C (32° to 104°F)

Storage Temperature: -40° to +70°C (-40° to 158°F)

Humidity: 10% to 90%, RHL non-condensing

General Product Dimensions (Diameter, H): 15.5cm x 14.6cmm (6.1" x 5.7")

Shipping Dimensions: 27.5cm x 22cm x 19.5cm (10.8" x 8.7" x 7.7") (W, D, H)

Product Weight: 1.32kg (2.9lbs) approx

Shipping Weight: 1.9kg (4.2lbs) approx



CONFIGURATIONS

RTBUS-28XL(B)	Round Table Connection Bus for Power Socket , USB Charging and Cable Pass-Throughs
RTBUS-28XL(BC)	Round Table Connection Bus for Power Socket , USB Charging and Cable Pass-Throughs

