

SMART Ultra HD Camera 120

SWC-120UHD



Overview

The SMART Ultra HD Camera 120 is a 4K Ultra-HD camera with ePTZ. Easily install the camera on a SMART Board® interactive display. The camera can automatically frame people meeting in a boardroom.

Image	
Sensor	1/2.8" 4K CMOS
Pixel count	8.28 megapixels
Aspect ratio	16:9
Video interface	1 channel USB 3.0 output, Type-B
View angle	138°(D) /120°(H)/68°(V)
Video compression format	MJPEG: Up to 3840 × 2160@30 fps
	H264: Up to 3840 × 2160@30 fps
	YUY2: Up to 1920 × 1080@30 fps
	NV12: Up to 1920 × 1080@30 fps

Optics	
Focal length	f=1.89mm
Aperture	F2.0±5%
Digital zoom	10×
Focus	Fixed
Backlight compensation	✓
Signal-to-noise ratio	≥ 50dB

Function	
Auto framing	✓
White balance	Auto
	Manual
Exposure	Auto
	Manual
	Shutter priority
	Brightness priority
USB communication protocol	UYC
ePTZ (pan, tilt, zoom control)	✓

Com		

Supported SMART hardware

SMART Board QX Pro series SMART Board 6000S (V3) and

6000S (V3) Pro series

SMART Board MX (V4) and MX (V4) $\,$

Pro series

SMART Board MX (V5) and MX (V5)

Pro series

SMART Board RX series

smarttech.com smarttech.com/contact

© 2024 SMART Technologies ULC. All rights reserved. SMART Board, smarttech, the SMART logo and all SMART taglines are trademarks or registered trademarks of SMART Technologies ULC in the U.S. and/or other countries. All third-party product and company names may be trademarks of their respective owners. This product and/or use thereof is covered by one or more of the following U.S. patents: www.smarttech.com/patents. Models and specifications may vary by region. Please contact your local representative for details. Contents are subject to change without notice. July 26, 2024.

docs.smarttech.com/kb/171857

Hardware requirements	
Supported operating systems	Windows® 10 or later macOS 10.10 or later Android™ 11 Linux® 4.9.84
Processor for Windows computers	2.4 GHz Intel®Core™ 2 Duo or faster
USB support for Windows computers	USB 3.0 for 4K resolution

Outputs	Qty
USB 3.0 Type-B	1

Included cables and accessories	Qty
10' (3 m) USB 3.0 Type-B to Type-A	1
1' (0.3 m) USB 3.0 Type-B to Type-C	1
Mounting hardware kit	1
Remote control	1
AAA batteries	2
Illustrated installation instructions	1
SMART Product card	1

Warranty

SMART Limited Equipment Warranty

Three years with purchasable two year extension.

Terms and conditions and warranty upgrade options vary by region.
Visit smarttech.com/warranty or contact your reseller for

information.

Power consumption	
Input voltage	5V
Input current	0.9A (maximum)

Storage and operating requirements

Operating temperature	14-122°F (-10-50°C)
Operating humidity	20–80% relative humidity, non-condensing
Storage temperature	14-140°F (-10-60°C)
Storage humidity	20–90% relative humidity, non-condensing

Certification and compliance	
US/Canada	FCC Part 15B, ICES-003, TSCA, CONEG Packaging, Proposition 65
EU/EEA/EFTA/UK	CE, UKCA, EMCD, REACH, RoHS, Battery, WEEE, Packaging, POP, EcoDesign
Australia/New Zealand	RCM
Regulatory model	C120-1

Purchasing information	
Order number: SWC-120UHD	SMART Ultra HD Camera 120
Ontional accessories	See smarttech com/accessories

docs.smarttech.com/kb/171857


Dimensions and weights

Note

All dimensions \pm 0.3 cm. All weights \pm 0.9 kg.

SWC-120UHD

Dimensions



Weight

0.5 lb. (0.23 kg)

Shipping dimensions

10.2" × 5.1" × 6.3" (26 cm x 13 cm x 9.5 cm)

Shipping weight

1.2 lb. (0.55 kg)

docs.smarttech.com/kb/171857