

HPE ProLiant DL360 Gen11 5416S 2.0GHz 16-core 1P 32GB-R NC 8SFF 800W PS Server (P51931-421)



What's new

- Powered by 4th Gen Intel® Xeon® Scalable processors with next-generation technology that supports up to 60 cores at 350W, and 16 DIMMs for up to 8 TB of high bandwidth DDR5 memory up to 4800 MHz.
- 16 DIMMs per processor for up to 8 TB total DDR5 memory per server with increased performance, High Bandwidth Memory (HBM) support, and lower power requirements.
- Advanced data transfer rates and higher network speeds from the PCIe Gen5 serial expansion bus, with up to 2 x16 PCIe Gen5 and 2 OCP slots.
- Includes the new HPE Integrated Lights-Out 6 (iLO 6) server management software that enables you to securely configure, monitor, and update your HPE ProLiant

Overview

Are you looking for a scalable, compute-dense solution for high-performance workloads such as VDI, EDA, or CAD?

The HPE ProLiant DL360 Gen11 server is a rack-optimized 1U dense solution that delivers exceptional compute performance, upgraded high-speed data transfer rate, and memory depth with 2P compute capability. Powered by 4th Gen Intel® Xeon® Scalable processors with up to 60 cores, increased memory bandwidth, up to 8 TB of memory, and high-speed PCIe Gen5 I/O, the HPE ProLiant DL360 Gen11 server is a perfect rack-optimized, 1U 2P, dense solution for general-purpose virtualization workloads that require increased compute density with built-in security and flexibility.

The silicon root of trust anchors the server firmware to an HPE-exclusive ASIC, creating an immutable fingerprint for the Secure Intel Processor that must be matched exactly before the server will boot. The HPE ProLiant DL360 Gen11 server is an excellent choice for EDA, CAD, and VDI.

Gen11 servers seamlessly, from anywhere.

- Supports up to 2 single wide (SW) GPUs[1] to accelerate graphic intense workloads.
- Supports Smart Cooling Modules for highest thermal design points (TDPs).

Features

Intuitive Cloud Operating Experience: Simple, Self-service, and Automated

HPE ProLiant DL360 Gen11 servers are engineered for your hybrid world. ProLiant DL360 Gen11 servers are powered by 4th Generation Intel® Xeon® processors and simplify the way you control your business's compute—from edge to cloud—with a cloud operating experience.

Transform business operations and pivot your team from reactive to proactive with global visibility and insight through a self-service console.

Automate tasks for efficiency in deployment, instant scalability, and seamless, simplified support and lifecycle management to reduce and shorten maintenance windows.

Self-service automated experiences are engineered and built into all HPE ProLiant Gen11 servers, whether purchased as physical servers or consumed as as-a-service using HPE GreenLake as your compute and storage demands grow.

Simplify and secure server management from edge to cloud with HPE GreenLake for Compute Ops Management. HPE GreenLake for Compute Ops Management is an as-a-service compute management experience that delivers greater simplicity, agility, and speed across your entire compute landscape, globally.

Trusted Security by Design: Uncompromising, Fundamental, and Protected

The HPE ProLiant DL360 Gen11 server utilizes the HPE Silicon Root of Trust, HPE's fundamental approach to security that provides zero-trust architecture at the silicon level and ensures all server essential firmware is free from malware or compromised code.

This server, powered by 4th Gen Intel® Xeon® Scalable Processors, adds hardware- and software-assisted security features, including Intel® Software Guard Extensions and Intel® Boot Guard, which help secure the server hardware foundation on which critical apps run and better protect data in memory.

HPE ProLiant Gen11 servers continuously protect healthy servers by a) providing rapid detection of security-compromised servers, even to the point of not allowing them to boot if it identifies malicious code, and b) securing servers at the edge with IDevID certificates installed by default.

HPE ProLiant Gen11 servers provide automated recovery from a security event, including restoration of validated firmware, and facilitating recovery of the operating system, application, and data connections, providing a fast path to bring a server back online and into normal operations.

Embedded in Hewlett Packard Enterprise servers, HPE Integrated Lights-Out 6 (iLO 6) is an exclusive core intelligence that monitors server status, providing the means for reporting, ongoing management, service alerting, and local or remote management to quickly identify and resolve issues.

Optimized Performance for your Workloads: Accelerated, Open, and Efficient

The HPE ProLiant DL360 Gen11 server is an excellent choice for EDA, CAD, and general-purpose virtualization workloads (including large-scale VDI), and Platforms (VCF & Containers) that require increased compute density with built-in security and flexibility.

Harness major computer performance. The HPE ProLiant DL360 Gen11 server is powered by the 4th Generation Intel® Xeon® Scalable Processors with next-generation technology that supports up to 60 cores, 350W, and up to 8 TB of memory.

The HPE ProLiant DL360 Gen11 server provides advanced data transfer rates and higher network speeds from the PCIe Gen5 serial expansion bus, with up to 2 x16 PCIe Gen5 and 2 OCP slots to improve I/O throughput and reduce latency.

The server provides 16 DIMMs per processor for up to 8 TB total DDR5 memory with increased memory bandwidth and performance, and lower power



requirements.

The HPE ProLiant DL360 Gen11 server provides real-time operational feedback on server performance plus recommendations for fine-tuning BIOS settings to customize for changing business needs.

Technical specifications

HPE ProLiant DL360 Gen11 5416S 2.0GHz 16-core 1P 32GB-R NC 8SFF 800W PS Server

Product Number	P51931-421
Processor name	Intel® Xeon® Gold 5416S (16 core, 2.0 GHz, 30 MB L3, 150W)
Processor number	1 processor included
Processor core available	16 core
Processor cache	30 MB L3
Processor speed	2.0 GHz
Power supply type	1x HPE 800W Flex Slot Titanium Hot Plug Low Halogen Power Supply Kit
Expansion slots	2-slots (x16 FH, x16 HH) as standard. Upgradeable to 3rd slot in HH (or remove Slot 2 bracket to be FH at Slot 3) in a 2nd processor configuration. And maximum 2 OCP 3.0 PCIe5 slots.
Memory type	HPE DDR5 SmartMemory
Included hard drives	None ship standard, 8 SFF supported
Optical drive type	Optional - HPE 9.5mm SATA DVD-RW Optical Drive, HPE Mobile USB DVD-RW Drive.
System fan features	Standard Fan Kit (Q'ty 5)
Network controller	Broadcom BCM57416 Ethernet 10Gb 2-port BASE-T Adapter for HPE
Storage controller	Embedded Intel® VROC SATA for HPE ProLiant Gen11, with 14 SATA ports (10-ports accessible) Choice of HPE modular Smart Array and PCIe plug-in controller
Product dimensions (metric)	24.1 x 60 x 99 cm
DIMM capacity	32 GB (1x 32 GB)
Weight	32.33 kg
Infrastructure management	Included - HPE iLO Standard with Intelligent Provisioning (embedded), HPE OneView Standard (requires download).
Warranty	3/3/3: Server Warranty includes three years of parts, three years of labor, and three years of onsite support coverage. Additional information regarding worldwide limited warranty and technical support is available at: https://h20564.www2.hpe.com/hpsc/wc/public/home . Additional HPE support and service coverage, to supplement the product warranty, is available. For more information, visit https://www.hpe.com/support



GPU support available Q2 2023. Subject to change.



For additional technical information, available models and options, please reference the [QuickSpecs](#)

**Make the right purchase decision.
Contact our presales specialists.**

[Chat online](#)



© Copyright 2023 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Parts and Materials: HPE will provide HPE-supported replacement parts and materials required to maintain the covered hardware.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product quick-specs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

Intel, Intel Xeon, and Intel Optane are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries. All third-party marks are property of their respective owners.

Image may differ from the actual product
[PSN1014731914UKEN](#), August, 2023.