



MAG A850GL PCIE5 WHITE

- ATX 3.0 compatible, native PCIe 5.0 connector
- Supports NVIDIA® GeForce RTX™ 40 Series graphics cards
- Full modular design, Flat cables
- 80 Plus Gold certified for high efficiency
- Active PFC design, Industrial level protection with OVP, OCP, OPP, OTP, SCP, UVP
- 120mm Fluid Dynamic Bearing Fan
- LLC Full Bridge Topology with DC-DC module design

SPECIFICATIONS

Efficiency Rating	80 PLUS Gold (up to 90%)
Modular	Yes (full modular)
Fan Size	120 mm
Fan Bearing	Fluid Dynamic Bearing
Dimensions (DxWxH)	140 x 150 x 86 mm
PFC Type	Active PFC
Input Voltage Range	100~240 VAC
Power Watt	850W
Power Excursion	1700W (*up to 200% of the PSU's rated power for 100µs)
Input Frequency Range	47-63Hz
Protection	OCP / OVP / OPP / OTP / SCP / UVP
ATX (24 pin)	1
EPS (4+4 pin)	2
PCI-E 5.0 (16 pin)	1 (600W)
PCI-E (6+2 pin)	4
SATA (15 pin)	8
MOLEX (4 pin)	4
FDD (4 pin)	1