

HyperDrive^{Next}

HD7001GL

Business Class 10 Port
USB-C Docking station

Dimensions:

Length x Width x Height (cm) – 17.0 x 8.3 x 1.7 cm

Weight (kg) - Approx. 0.240 Kg (USB-C cable – 9 g)

SRP: £179.99 | €199.99



Product Specification – HD7001GL

Connection to host device		Host system OS compatibility	
Connector type	USB-C* - via USB-C to USB-C cable included	Works with Windows®	•
Connector technology	USB 3.2 Gen 2 (10 Gbps)	Works with MacOS®	•
Graphics Technology	Hybrid - DP Alt Mode + SiliconMotion® USB Graphics	Works with ChromeOS®	• ****
		Works with iOS®	--
		Works with Android®	--
		Works with Samsung DEX	--
		Works With Linux Ubuntu™	--
Host device port compatibility		Device compatibility	
USB 3	•	Windows® Laptop	•
USB4	•	Microsoft Surface® Laptop	•
Thunderbolt 3	•	ChromeBook®	•
Thunderbolt 4	•	Apple iMac®	--
Video ports		Apple MacBook Pro® / Air® 2016 - 2019	•
HDMI	1x HDMI 2.0 - DP Alt mode 1x HDMI 1.4 - USB Graphics	Apple MacBook Pro® / Air® M1 / M2 2020 - 2022	•
Display Port	--	Apple MacBook Pro® / M1 / M2 Pro / Max 2021 - 2023	•
VGA	--	Apple iPad Pro® 2018 or later	--
Video via High-speed USB / Thunderbolt port	--	Apple iPad Air® 2020 or later	--
Maximum no. of monitor(s)	2	Android® Tablet	--
Maximum resolution (single monitor)	4K @ 60 Hz via DP Alt Mode 4K @ 30 Hz via USB Mode**	Android® Smartphone	--
Maximum resolution (multi-monitor)	4K @ 60 Hz + 4K @ 30 Hz**		
HDR via HDMI	--		
Connection Ports		Other features	
USB-A (Power / Max data speed)	2x USB 3.2 Gen2 (10 Gbps)	On/ Off Switch	•
	1x USB 3.2 Gen2 (100 W PD / 10 Gbps) to host	PXE Boot	• *****
USB-C (Power / Max data speed)	1x USB 3.2 Gen2 (10 Gbps) 1x USB PD 3.0 (Max. 100 W)	Wake-on LAN	•
Thunderbolt 3	--	LAN/ WLAN Switching	• *****
Thunderbolt 4	--	Mac Address passthru	• *****
RJ45 Ethernet	Gigabit Ethernet		
3.5 mm Audio	•	Security cable lock slot	1x Kensington® standard K slot 1x Kensington® Nano slot
Other audio ports	--	Compatible cable locks	• - Targus ASP9 series Universal lock
Memory cards	SD/ MicroSD 4.0 (312 MB/s) - UHS-II card compatible *****	Construction material	Up to 85% PCR recycled plastics where applicable
		VESA mount compatible	--
Power		USB-C [to host device] cable	Detachable USB-C to USB-C cable (included)
USB Power Delivery to host device	- when hub is connected to optional USB-C PD 3.0 charger or HJ8003 AC adapter*** USB-C PD 3.0 charger- 100 W PD 3.0 / up to 85 W pass through to host device	Warranty	2 years
Max. PD power / PD pass through to host	HJ8003 AC adapter - 150 W adapter / guaranteed up to 100 W to host device	Content	
Recommended USB-C chargers		• HD7001GL Business Class 10 port USB-C Docking Station	
Hyper HJG100 100 W GaN charger	•	• USB-C to USB-C cable	
Hyper HJG140 140 W Universal GaN charger	•	• User Guide	
Targus APA108 100 W laptop charger	•	Notes	
		*Full hub data, video and power functionality will require host device with USB-C port compatible with DP Alt Mode, Power Delivery PD 3.0 and USB 3.2 Gen1 / Gen2	
		** Using extended desktop mode onto dual monitor requires HDMI port supporting USB mode to be active via Intel/View driver download from http://www.siliconmotion.com/downloads/index.html . Single monitor connection via HDMI port supporting DP Alt Mode only without Intel/View driver active even with both HDMI ports on docking station are connected to compatible external monitors	
		*** Compatible with optional 100 W USB-C PD charger with up to 85 W pass through to device or optional 150 W AC adapter HJ8003	
		**** Requires ChromeOS version R69 or later	
		***** Maximum SD / MicroSD 4.0 transfer speed requires UHS-II compliant SD / MicroSD cards. Actual transfer speed depends SD / MicroSD card read and write speed specifications and host device processor and port capability	
		***** Supported via device OS settings	