

GeForce RTX™ 4080 16GB GAMING X SLIM WHITE










SPECIFICATIONS

Model Name	GeForce RTX™ 4080 16G GAMING X SLIM WHITE
Graphics Processing Unit	NVIDIA® GeForce RTX™ 4080 16GB
Interface	PCI Express [®] Gen 4
Core Clocks	Extreme Performance: 2610 MHz (MSI Center) Boost: 2595 MHz (GAMING & SILENT Mode)
CUDA® CORES	9728 Units
Memory Speed	22.4 Gbps
Memory	16GB GDDR6X
Memory Bus	256-bit
Output	DisplayPort x 2 (v1.4a) HDMI [™] x 2 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI [™] 2.1a)
HDCP Support	Υ
Power consumption	320 W
Power connectors	16-pin x 1
Recommended PSU	850 W (Min.750 W)
Card Dimension (mm)	322 x 136 x 62 mm
Weight (Card / Package)	1673 g / 2545 g
DirectX Version Support	12 Ultimate
OpenGL Version Support	4.6
Maximum Displays	4
G-SYNC® technology	Υ
Digital Maximum Resolution	7680 x 4320

CONNECTIONS



FEATURES



TRI FROZR 3

Stay cool and quiet. MSI's TRI FROZR 3 thermal design enhances heat dissipation all around the graphics card.



Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



Copper Baseplate

Heat from the GPU and memory modules is captured by a copper baseplate and then rapidly transferred to Core Pipes.



Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.



Airflow Control

Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.



Metal Backplate

Thermal pads under the sturdy metal backplate provide additional cooling while the flow-through ventilation reduces trapped heat.



Dual BIOS

Dual BIOS lets you set the priority to full performance in GAMING mode or low noise in SILENT mode.



MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.