

# Cables ExCam

## Power and data cables for hazardous areas

Two types of data and power cables (armored and non-armored), specially designed for hazardous areas in accordance with EN 60079-14 for use in arctic temperatures (-60 °C/-76 °F). The cables are ideal for wiring explosion-protected network cameras in ExCam series. They are high-speed cables for Industrial Ethernet for fixed installations in dry, wet, or damp rooms. The cables meet the transmission characteristics for Category 6 of IEC 61156-5 Edition 2. Both cables are available in different lengths: 10 m (33 ft), 25 m (82 ft), and 95 m (312 ft).

- > [Armored and non-armored types](#)
- > [Several cable lengths](#)
- > [Compatible with ExCam series](#)



## SKDP03-T Cable ExCam (non-armored)

General		Storage conditions	-10 °C to 50 °C (14 °F to 122 °F) Humidity 30–70% RH (non-condensing)
Supported products	Explosion-protected cameras	Approvals	IEC/EN 60079-14, EN 50288-10-1, IEC 61156-5, EN 50173, ISO/IEC 11801 2. edition, EN 60332-1-2, IEC 60754-2, UL AWM 21586 RoHS 2011/65/EU, IEC 60811-2-1 (IRM 902, 4h at 70°C)
Casing	PUR FHF Color: RAL 6018 Bending radius: 10 x diameter during installation, 5 x diameter after installation Maximum tractive force: 300 N (67 lbf)	Environment	UV-resistant, suitable for outdoor use
Sustainability	PVC free	Dimensions	ø 12.3 mm (1/2 in) Length: 10 m (33 ft), 25 m (82 ft), or 95 m (312 ft)
Connectors	RJ45 10BASE-T/100BASE-TX/1000BASE-T CAT6, 4x2xAWG22 3G1.5	Weight	<b>10 m (33 ft):</b> 1.9 kg (4.2 lb) <b>25 m (82 ft):</b> 4.3 kg (9.5 lb) <b>95 m (312 ft):</b> 15.5 kg (34.2 lb)
Operating conditions	-60 °C to 80 °C (-76 °F to 176 °F) <b>During installation:</b> -10 °C to 50 °C (14 °F to 122 °F) Humidity 10–100% RH (condensing)	Included accessories	1x Ex d cable gland (M20x1.5) with compound and connector kit, 1x Cat 6 RJ45 connector, thread lock, installation guide
		Warranty	Axis 3-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>

## ASKDP03-T Armored Cable ExCam (armored)

General		Approvals	IEC/EN 60079-14, EN 50288-10-1, IEC 61156-5, EN 50173, EN 50174, ISO/IEC 11801 2. edition, EN 60332-1-2, IEC 60754-2, UL AWM 21586 RoHS 2011/65/EU, IEC 60811-2-1 (IRM 902, 4h at 70°C)
Supported products	Explosion-protected cameras	Environment	UV-resistant, suitable for outdoor use
Casing	PUR FHF Color: RAL 6018 Bending radius: 10 x diameter during installation, 5 x diameter after installation Maximum tractive force: 550 N (124 lbf)	Dimensions	ø 17 mm (11/16 in) Length: 10 m (33 ft), 25 m (82 ft), or 95 m (312 ft)
Sustainability	PVC free	Weight	<b>10 m (33 ft):</b> 3.9 kg (8.6 lb) <b>25 m (82 ft):</b> 9.2 kg (20 lb) <b>95 m (312 ft):</b> 33.7 kg (74.3 lb)
Connectors	RJ45 10BASE-T/100BASE-TX/1000BASE-T CAT6, 4x2xAWG22 3G1.5	Included accessories	1x Ex e cable gland (M20x1.5), 1x Ex d cable gland (M20x1.5) with compound and connector kit, 1x Cat 6 RJ45 connector, thread lock, installation guide
Operating conditions	-60 °C to 80 °C (-76 °F to 176 °F) <b>During installation:</b> -10 °C to 50 °C (14 °F to 122 °F) Humidity 10–100% RH (condensing)	Warranty	Axis 3-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>
Storage conditions	-10 °C to 50 °C (14 °F to 122 °F) Humidity 30–70% RH (non-condensing)	<b>Environmental responsibility:</b> <a href="http://www.axis.com/environmental-responsibility">www.axis.com/environmental-responsibility</a>	