

V228 LTE-SPECS

ID	V228 LTE Version	
ChipSet	PCBA	SPT117
General	2G Network	GSM850/900/1800/1900
	3G Network	B1+B8
	4G Network	B1+B3+B7+B8+B20
	SIM	Single Nano
Body	Dimensions	102*55.1*20.3mm
	Weight	TBD
	Type	Flip Senior
Display	Main Type	TFT
	Size	2.8' (240*320)
	Sub type	OLED(4-wire SPI ,I2C)
	Size	1.1"(Dot matrix:128Wx36H)
Camera	Pixels	2M
Sound	Alert types	Ringtones Vibration
	Loudspeaker	1712 box Speaker(Drived by an external Class K)
	Receiver	1508HAC
	Type C headset	Yes
Memory	Internal	64MB+128MB
	External	T-flash card
Data	GPRS/Edge/HSPA/LTE	Yes
	WLAN	No
	GPS	No
	Bluetooth	Yes
	USB	Yes, Type C
Features	Messaging	SMS,MMS
	FM Radio	Yes(Headset as antenna)
	Sensor	Hall(POSITION same as V227)
	Torch	YES(doesn't share pin with 3-LED.
	Indicator LED	NA
	Keys	2 sidekeys more based on V227-4G, camera and Torch.
	keypad Backlight	LEDs location is exactly the same as V227.
Battery	SOS	YES
	Type	Li-ion
	capatity	1300mAh (500 cycle 80%capacity remain)
	Stand-by	Up to 15 days
Artwork	Talk time	Up to 360 Mins
	Body housing	as customer's requirments
Accessories	charger	5V/0.5A ErP VI x1
	battery Cover	X2 one with SOS hole /One without hole
	gift box	x1
	user manual	x1
	warranty card	x1
	earphone	x1
	Cable Type C	x1
	Cradle (with detection) Type C	X1
	battery	x1
Certification	HAC M4/T4	Yes
	Reach&Rohs	Yes
	CE-RED	Yes
	GCF	Yes

