



# Plugable Technologies 5-in-1 USB C Hub Multiport Adapter for MacBook Pro 14/16 Inch, Macbook Air M2 - USB-C 40Gbps Port Compatible with Thunderbolt/USB4 and 100W PD, Supports MagSafe (Ethernet, 2x USB), Driverless




**Brand :** Plugable Technologies

**Product code:** AMS-5IN1E

**Product name :** 5-in-1 USB C Hub Multiport Adapter for MacBook Pro 14/16 Inch, Macbook Air M2 - USB-C 40Gbps Port Compatible with Thunderbolt/USB4 and 100W PD, Supports MagSafe (Ethernet, 2x USB), Driverless

5-in-1 USB C Hub Multiport Adapter for MacBook Pro 14/16 Inch, Macbook Air M2 - USB-C 40Gbps Port Compatible with Thunderbolt/USB4 and 100W PD, Supports MagSafe (Ethernet, 2x USB), Driverless. Connectivity technology: Wired, Host interface: USB4, USB Power Delivery up to: 100 W. Ethernet LAN data rates: 10,100,1000 Mbit/s, Copper ethernet cabling technology: 1000BASE-T. Product colour: Silver, Data transfer rate: 40 Gbit/s, HD type: 6K Ultra HD. Width: 108 mm, Depth: 37 mm, Height: 13 mm. Chipset: KTMicro - KT0200, ASIX - AX88179A



Ports & interfaces		Performance	
Connectivity technology *	Wired	Card reader integrated *	✗
Host interface *	USB4	Data transfer rate	40 Gbit/s
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	2	HD type	6K Ultra HD
USB4 ports quantity	1	Maximum digital resolution	6016 x 3384 pixels
USB Power Delivery	✓	Maximum refresh rate	60 Hz
USB Power Delivery up to	100 W	Product colour *	Silver
DisplayPort version	1.4	Brand compatibility	Apple
Combo headphone/mic port	✓	Compatibility	2021 14" M1 MacBook Pro 2021 16" M1 MacBook Pro 2022 M2 MacBook Air 2023 14" M2 MacBook Pro 2023 16" M2 MacBook Pro 2023 14" M3 MacBook Pro 2023 16" M3 MacBook Pro
Headphone outputs *	1		
Headphone connectivity	3.5 mm		
HDCP	✓		
USB Type-C DisplayPort Alternate Mode	✓		
Network		Weight & dimensions	
Ethernet LAN *	✓	Width	108 mm
Ethernet LAN (RJ-45) ports	1	Depth	37 mm
Ethernet LAN data rates	10,100,1000 Mbit/s	Height	13 mm
Copper ethernet cabling technology	1000BASE-T	Weight	40 g
		Packaging content	
		Quick start guide	✓
		Other features	
		Chipset	KTMicro - KT0200, ASIX - AX88179A



0819927012962



819927012962

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 30-OCT-2024. Prints or copies of Information are only valid on the printed Publication date