

TP-Link Archer AX3000 Dual-Band Wi-Fi 6 Air Router

Brand : TP-Link

Product family: Archer

Product code: ARCHER AIR R5

Product name : AX3000 Dual-Band Wi-Fi 6 Air Router

- Next-Gen Gigabit Wi-Fi 6 Speed—2402 Mbps on 5 GHz and 574 Mbps on 2.4 GHz band ensure smoother streaming and faster downloads

- Smart Antennas - Uses intelligent algorithms to auto-detect your devices' locations and adjust

antennas' direction for all-round stable signals

- Ultra-Low Latency—Enables more responsive gaming and video chatting

- TP-Link HomeShield - Enhanced security defends against the latest cyber threats

- EasyMesh-Compatible - Works with EasyMesh-compatible routers to create a whole home seamless mesh network

- Flexible Installation – Easy to stick or mount on the wall with 3M adhesives and the attached plastic bracket

AX3000, Wi-Fi 6, 2.4/5 GHz, 574 + 2402 Mbps, 1x Gigabit WAN, 1x Gigabit, 210 x 148 x 10.8 mm





WAN connection		Management features	
Ethernet WAN * DSL WAN *	×	WPS push button	4
		Security	
SIM card slot * 3G/4G USB modem compatibility *	× ×	Security algorithms	WPA, WPA-PSK, WPA2, WPA2-PSK, WPA3
WAN connection type	RJ-45	Guest access	1
Wireless LAN features		Protocols	
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz) Wi-Fi 6 (802.11ax) 2976 Mbit/s 802.11a, 802.11b, 802.11g, Wi-Fi 4	DHCP server	1
Top Wi-Fi standard *		Supported network protocols	IPv4, IPv6
WLAN data transfer rate (max) *		Design	
Wi-Fi standards	(802.11n), Wi-Fi 5 (802.11ac), Wi-Fi	Product colour	White
	6 (802.11ax)	Wall mountable	✓
WLAN data transfer rate (first band)	574 Mbit/s	Product type *	Tabletop router
WLAN data transfer rate (second band)	2402 Mbit/s	Certificates	
Network		Certification	FCC, CE, RoHS
Ethernet LAN *	1	Packaging content	
Ethernet LAN interface type *	Gigabit Ethernet	Manual	∢
Ethernet LAN data rates	10,100,1000 Mbit/s	Antenna	
Number of guest networks (2.4 GHz)	1	Antenna design *	Internal
Number of guest networks (5 GHz)	1	Power	
Ports & interfaces		Power source type *	USB
Ethernet LAN (RJ-45) ports *	1	Operational conditions	
USB port *	1	Operating temperature (T-T)	0 - 40 °C
USB charging port	4	Storage temperature (T-T)	-40 - 60 °C
Management features		Operating relative humidity (H-H)	10 - 90%
Quality of Service (QoS) support	1	Storage relative humidity (H-H)	5 - 90%
Reset button	1	Weight & dimensions	
		Width	148 mm
		Depth	10.8 mm
		Height	210 mm

Packaging data

Package type

Box





4895252500653

4895252500660

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.