



AOC E3 24E3QAF LED display 60.5 cm (23.8") 1920 x 1080 pixels Full HD LCD Black

Brand : AOC

Product family: E3

Product code: 24E3QAF

Product name : 24E3QAF

Screen size (inch) 23.8, Panel resolution 1920x1080, Max Refresh rate 75 Hz, Panel type IPS, HDMI HDMI 1.4 x 1, DisplayPort DisplayPort 1.2 x 1, D-SUB (VGA) 1x, DVI 0x, Sync technology (VRR) Adaptive Sync AOC E3 24E3QAF. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). VESA mounting, Height adjustment. Product colour: Black



Display		Ergonomics	
Display diagonal *	60.5 cm (23.8")	Cable lock slot *	✓
Display resolution *	1920 x 1080 pixels	Cable lock slot type	Kensington
HD type *	Full HD	Height adjustment *	✓
Native aspect ratio *	16:9	Height adjustment	15 cm
Display technology *	LCD	Pivot	✓
Panel type *	IPS	Pivot angle	-90 - 90°
LED backlight	✓	Swivelling	✓
Backlight type	W-LED	Swivel angle range	0 - 180°
Touchscreen *	✗	Tilt adjustment	✓
Response time *	4 ms	Tilt angle range	-5 - 35°
Anti-glare screen	✓	On Screen Display (OSD)	✓
Screen shape *	Flat	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish
Contrast ratio (typical) *	1000:1	Number of OSD languages	16
Contrast ratio (dynamic)	20000000:1	Plug and Play	✓
Maximum refresh rate *	75 Hz	LED indicators	✓
Viewing angle, horizontal	178°		
Viewing angle, vertical	178°		
Pixel pitch	0.2745 x 0.2745 mm		
Pixel density	93 ppi		
Horizontal scan range	30 - 85 kHz		
Vertical scan range	48 - 75 Hz		
Viewable size, horizontal	52.7 cm		
Viewable size, vertical	29.6 cm		
Digital horizontal frequency	30 - 85 kHz		
Digital vertical frequency	48 - 75 Hz		
Display diagonal (metric)	60.47 cm		
High Dynamic Range (HDR) supported	✓		
DDC/CI	✓		
		Power	
		Power consumption (typical) *	18 W
		Power consumption (standby) *	0.5 W
		Power consumption (max)	35 W
		Power consumption (off)	0.3 W
		AC input voltage	100 - 240 V
		AC input frequency	50/60 Hz
		Input current	1.5 A
		Power supply type	Internal

Display		Operational conditions	
Surface hardness	3H	Operating temperature (T-T)	0 - 40 °C
Grayscale depth	8 bit	Storage temperature (T-T)	-25 - 55 °C
Performance		Operating relative humidity (H-H)	10 - 85%
Fast charging	✗	Storage relative humidity (H-H)	5 - 93%
VESA Adaptive Sync support	✓	Operating altitude	0 - 5000 m
Flicker-free technology	✓	Non-operating altitude	0 - 12192 m
Low Blue Light technology	✓	Weight & dimensions	
Game mode	✓	Width (with stand)	540 mm
Multimedia		Depth (with stand)	200.1 mm
Number of speakers	2	Height (with stand)	503.6 mm
Built-in speaker(s) *	✓	Weight (with stand)	4.45 kg
Built-in microphone	✗	Width (without stand)	540 mm
Built-in camera *	✗	Depth (without stand)	50.7 mm
Design		Height (without stand)	362.3 mm
Market positioning *	Office	Weight (without stand)	2.63 kg
Product colour *	Black	Packaging data	
Frameless design	✓	Package width	613 mm
Front bezel colour	Black	Package depth	162 mm
Detachable stand	✓	Package height	519 mm
Feet colour	Black	Package weight	7.14 kg
Ports & interfaces		Packaging content	
Built-in USB hub *	✗	Stand included	✓
VGA (D-Sub) ports quantity	1	Cables included	AC, DisplayPort, HDMI
HDMI *	✓	Quick start guide	✓
HDMI ports quantity	1	Sustainability	
HDMI version	1.4	Sustainability compliance	✓
DisplayPorts quantity	1	Sustainability certificates	EPEAT Silver, TCO
DisplayPort version	1.2	Other features	
Audio input	✓	FPS counter	✓
Headphone out *	✓	Dial point	✓
Headphone outputs	1	Shadow control	✓
Headphone connectivity	3.5 mm	Compatibility	VESA-P2
HDCP	✓	Exterior finish type	Textured
HDCP version	1.4	Recyclable packaging material	100%
AC (power) in	✓	Warranty period	3 year(s)
Mobile High-Definition Link (MHL)	✗	Compliance certificates	CB, CE, EAC, Federal Communications Commission (FCC), RoHS, cTUVus, WEEE
Ergonomics		Light effects	✗
VESA mounting *	✓	Certification	ISO 9241-307
Panel mounting interface	100 x 100 mm	Recycling data	
Cable management	✓	Post-consumer recycled plastic	85%



4038986141253

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 30-OCT-2024. Prints or copies of Information are only valid on the printed Publication date