



i-tec USB-C Metal Ergonomic 3x 4K Display Docking Station + Power Delivery 100 W



Brand : i-tec

Product code: C31FLAT2PDPRO

Product name : USB-C Metal Ergonomic 3x 4K Display Docking Station + Power Delivery 100 W

- Docking station that can also be used as a laptop stand
 - Compatible with USB-C and Thunderbolt laptops and tablets (Host device must support DisplayPort Alt mode)
 - 2x DisplayPort and 1x HDMI support up to three external 4K displays or one 5K/60Hz display. (macOS only supports one extended display)
 - Ergonomic design with aluminium housing, the dock has an integrated 60cm USB-C cable, making it suitable for use with all laptops & tablets with displays up to and including 15"
 - Including 4x USB 3.2 ports and SD and microSD card slots makes it easy to connect multiple USB devices and peripherals
 - Provides up to 100W Power Delivery for compatible laptops and tablets with USB-C and Thunderbolt (Host device must support USB-C Power Delivery)
 - GLAN Ethernet supports network speeds of 10/100/1000 Mbps and provides robust, high-speed Internet connectivity
 - Combined 3.5mm audio input/output for easy connection of headset or speakers
- USB-C Metal Ergonomic 3x 4K Display Docking Station + Power Delivery 100 W

Ports & interfaces		Software	
Connectivity technology *	Wired	Windows operating systems supported	✓
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C	Mac operating systems supported	✓
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	4	Linux operating systems supported	✓
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1	Other operating systems supported	Android, ChromeOS
USB Power Delivery	✓	Operational conditions	
USB Power Delivery up to	100 W	Operating temperature (T-T)	0 - 40 °C
HDMI ports quantity *	1	Operating relative humidity (H-H)	10 - 100%
DisplayPorts quantity	2	Weight & dimensions	
Combo headphone/mic port	✓	Width	270 mm
Network		Depth	85 mm
Ethernet LAN *	✓	Height	23 mm
Ethernet LAN (RJ-45) ports	1	Weight	268 g
Ethernet LAN data rates	10,100,1000 Mbit/s	Packaging data	
Performance		Package width	316 mm
Card reader integrated *	✓	Package depth	130 mm
Compatible memory cards	MicroSD (TransFlash), SD	Package height	30 mm
Data transfer rate	5 Gbit/s	Packaging content	
Number of displays supported	3	AC adapter included	✗
Product colour *	Silver	Manual	✓
Power			
USB cable length	0.6 m		



8595611706530

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 30-OCT-2024. Prints or copies of Information are only valid on the printed Publication date