



## AOC G3 U32G3X/BK LED display 80 cm (31.5") 3840 x 2160 pixels 4K Ultra HD Black, Red

Brand : AOC

Product family: G3

Product code: U32G3X/BK

Product name : U32G3X/BK

Screen size (inch) 31.5, Panel resolution 3840x2160, Refresh rate 144 Hz, Response time MPRT 1 ms, Panel type IPS, HDMI HDMI 2.1 x 2, Display Port DisplayPort 1.4 x 2, Sync technology (VRR) G-SYNC Compatible + Adaptive Sync

AOC G3 U32G3X/BK LED display 80 cm (31.5") 3840 x 2160 pixels 4K Ultra HD Black, Red:


### Take your gaming adventures to new heights with the G-sync compatible monitor, U32G3X/BK, offering an impressive 31.5-inch display that delivers stunning 4K UHD resolution at 3840x2160

The G-Sync compatible U32G3X/BK boasts a remarkable 31.5-inch display, showcasing stunning 4K UHD resolution at 3840x2160 for an unrivaled level of visual clarity. With an ultra-responsive 1ms GtG response time and a high 144Hz refresh rate, this monitor redefines your gameplay. Immerse yourself in the heat of battle or explore vast virtual worlds with unmatched precision and smoothness.



Display		Ergonomics	
Display diagonal *	80 cm (31.5")	Cable lock slot *	✓
Display resolution *	3840 x 2160 pixels	Cable lock slot type	Kensington
HD type *	4K Ultra HD	Height adjustment *	✓
Native aspect ratio *	16:9	Height adjustment	13 cm
Display technology *	LED	Pivot	✗
Panel type *	IPS	Swivelling	✓
Backlight type	W-LED	Swivel angle range	-30 - 30°
Touchscreen *	✗	Tilt adjustment	✓
Display brightness (typical)	350 cd/m <sup>2</sup>	Tilt angle range	-5 - 23°
Response time *	1 ms	Picture-in-Picture	✓
Anti-glare screen	✓	On Screen Display (OSD)	✓
Screen shape *	Flat	On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Croatian, Czech, German, Dutch, English, Spanish, Finnish, French, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Contrast ratio (typical) *	1000:1		
Contrast ratio (dynamic)	80000000:1		
Maximum refresh rate *	144 Hz		
Viewing angle, horizontal	178°		
Viewing angle, vertical	178°		
Display number of colours *	1.07 billion colours		
Pixel pitch	0.181 x 0.181 mm		
Pixel density	139 ppi		
Viewable size, horizontal	69.7 cm		
Viewable size, vertical	39.2 cm		
Display diagonal (metric)	80 cm		
High Dynamic Range (HDR) supported	✓		
High Dynamic Range (HDR) technology	DisplayHDR 400		
Surface hardness	3H		
sRGB coverage (typical)	122%		
NTSC coverage (typical)	107%		
		Power	
		Energy efficiency class (SDR) *	F
		Energy efficiency class (HDR) *	G
		Energy consumption (SDR) per 1000 hours *	32 kWh
		Energy consumption (HDR) per 1000 hours *	65 kWh
		Power consumption (typical) *	40 W
		Power consumption (standby) *	0.5 W
		Power consumption (off)	0.3 W
		AC input voltage	100 - 240 V
		AC input frequency	50/60 Hz
		Input current	1.5 A

<b>Display</b>		<b>Power</b>	
DCI-P3 coverage	95%	Energy efficiency scale	A to G
<b>Performance</b>		European Product Registry for Energy Labelling (EPREL) code	1711583
NVIDIA G-SYNC *	✓	<b>Weight &amp; dimensions</b>	
VESA Adaptive Sync support	✓	Width (with stand)	715.3 mm
Low Blue Light technology	✓	Depth (with stand)	258.8 mm
Game mode	✓	Height (with stand)	587.1 mm
<b>Multimedia</b>		Weight (with stand)	7.79 kg
Built-in speaker(s) *	✗	Width (without stand)	421.8 mm
Built-in camera *	✗	Depth (without stand)	47.6 mm
<b>Design</b>		Height (without stand)	715.3 mm
Market positioning *	Gaming	Weight (without stand)	6.41 kg
Product colour *	Black, Red	<b>Packaging data</b>	
Frameless design	✓	Package weight	10.9 kg
Front bezel colour	Black/Red	<b>Packaging content</b>	
Detachable stand	✓	Stand included	✓
Feet colour	Black, Red	Cables included	AC
<b>Ports &amp; interfaces</b>		DisplayPort cable length	1.8 m
Built-in USB hub *	✗	HDMI cable length	1.8 m
HDMI *	✓	<b>Sustainability</b>	
HDMI ports quantity	2	Sustainability compliance	✓
HDMI version	2.1	<b>Other features</b>	
DisplayPorts quantity	2	Low input lag	✓
DisplayPort version	1.4	FPS counter	✓
Headphone out *	✓	Dial point	✓
Headphone outputs	1	Shadow control	✓
Headphone connectivity	3.5 mm	Motion blur reduction	✓
HDCP	✓	Local dimming zones	16
HDCP version	2.2	Picture-by-Picture (PbP)	✓
<b>Ergonomics</b>		Digital signal format system	Not supported
VESA mounting *	✓	Exterior finish type	Textured
Panel mounting interface	100 x 100 mm	Bezel thickness type	Frameless
		Compliance certificates	WEEE



4038986111430

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 30-OCT-2024. Prints or copies of Information are only valid on the printed Publication date