

# Outdoor Pan/Tilt Security Wi-Fi Camera

2K  
QHD

Tapo C520WS

 Starlight Color Night Vision

Person/Pet/  
Vehicle Detection

Smart Motion  
Tracking

Local microSD Storage  
(Up to 512 GB)\*




works with | 

works with |  Google Home

## // Highlights

### 2K QHD, Starlight Color Night Vision

Equipped with an F1.6 large-aperture lens and starlight sensor, Tapo C520WS enhances your security by revealing highly-detailed and bright-color images even under low-light conditions.



### Person/Pet/Vehicle Detection and Notification

Smart AI identifies people, pets, and vehicles, notifying users as needed.



## // Features

### 360° Visual Coverage

Provides 360° horizontal & 130° vertical view (180° vertical view in Privacy Mode) range to capture everything around.

### IP66 Weatherproof

Offers excellent waterproof and dustproof performance for outdoor scenarios.

### Local<sup>†</sup> and Cloud<sup>‡</sup> Storage

Save recorded videos to an installed microSD card (up to 512 GB), or use Tapo Care cloud storage service.

### Multiple Installation Options

Use the mounting screws, template and loops<sup>‡</sup> to install on any wall, ceiling or pole for the perfect view—wherever you want.

### Two-Way Audio

Enables communication through a built-in microphone and speaker.

### Dual Powerful Antennas

Two external antennas ensure a powerful and stable wireless connection.

### Wired/Wireless Networking

Connect the camera to your network through Ethernet or Wi-Fi for more flexible installation.

### Customizable Sound and Light Alarm

Records your customized audio as an alarm to extend your usage. Set to trigger a light/sound alarm when detecting activity.

## // Specifications

### Camera

- Image Sensor: 1/3" CMOS
- Lens: F/NO:  $1.61 \pm 10\%$ ; Focal Length:  $3.18\text{mm} \pm 5\%$
- Video Definition: 2K QHD 4MP (2560 × 1440 px)
- Field of View: 360° Horizontal
- Night Vision: 850 nm IR LED (up to 98 ft), Starlight Color Night Vision

### Audio

- Audio Communication: 2-way audio
- Audio Input & Output: Built-in microphone and speaker

### Video

- Video Compression: H.264
- Frame Rate: Up to 25/30fps\*
- Video Streaming: 2K

### Activity Notifications

- Input Trigger:  
Motion detection, Person detection, Pet detection, Vehicle detection, Line-Crossing detection
- Output Notification: Notification, Snapshot(Tapo care), Clips(Tapo care)

### Network

- Wireless Protocols: IEEE 802.11b/g/n, 2.4 GHz
- Frequency: 2.4 GHz
- Wireless Security: WPA/WPA2-PSK
- Security: 128 bit AES encryption with SSL/TLS
- Protocol: TCP/IP, ICMP, DNS, HTTPS, TCP, UDP

## // Specifications

### Hardware

- Button: RESET button
- Indicator LED: System LED
- Adapter Input: 100-240V, 50/60Hz
- Adapter Output: 9V, 0.85A (DC Power)
- Typical Power Consumption: 3.75 W
- Maximum Power Consumption: 7.65 W
- External Storage: microSD card slot (Supports up to 512 GB)<sup>†</sup>
- Dimensions (W x D x H): 4.9 x 4.8 x 3.5 in. (123.8 x 123 x 90 mm)
- Weatherproof Rating: IP66
- Power Cord Length: 3 m

<sup>†</sup>Frame rate varies at different frequencies. Frame Rate is up to 25fps at 50Hz and 30fps at 60Hz.

<sup>†</sup>microSD card needs to be purchased separately.

<sup>††</sup>Tapo Care needs to be subscribed separately.

For more information, please visit <https://www.tapo.com/>

All brands and product names are trademarks or registered trademarks of their respective holders. Specifications are subject to change without notice.


©2023 TP-Link

### Others

- Certification: CE, FCC, RoHS, RCM
- Package Contents:
 

Tapo C520WS Camera ×1	Bracket Screws × 2
Power Adapter ×1	Waterproof Seal ×1
Mounting Template ×1	Waterproof Cable Attachments ×1
Mounting Bracket ×1	Quick Start Guide
Mounting Anchors ×4	
Mounting Screws ×4	
- Operating Temperature: -30 °C ~ 60 °C (-22 °F ~ 140 °F)
- Storage Temperature: -40 °C ~ 60 °C (-40 °F ~ 140 °F)
- Operating Humidity: 10%~90%RH, Non-condensing
- Storage Humidity: 0~90%RH, Non-condensing

## // Appearance



**1** Lens

**2** White Light LEDs

**3** IR LEDs

**4** System LED

**5** Microphone

**6** Reset

Loosen the screws. While the camera is powered on, use a pin to press and hold the Reset button for at least 5 seconds until the System LED blinks red. The camera will reset and reboot.

**7** microSD Card Slot

Loosen the screws and insert a microSD card\*. Initialize it on the Tapo app for local recording.

\*microSD card not included

**8** Speaker

**9** Ethernet Port

Used to connect to a network device

**10** DC Power Connector

Used to connect to a 9V DC power adapter