

# AXIS T8154 60 W SFP Midspan

## For network or fiber installations

AXIS T8154 60 W SFP Midspan is a compact, plug-and-play media converter with PoE. With its integrated power supply, it minimizes the amount of cabling and facilitates installation. AXIS T8154 offers data input through SFP or RJ45, and delivers PoE up to 60 W. It works with all Axis network products supporting Power over Ethernet.

- > SFP slot for fiber
- > Integrated midspan
- > PoE up to 60 W
- > Support for all Axis network products



Data



PoE



## AXIS T8154 60 W SFP Midspan

Midspans		General	
Function	Data and power are fed to a network video product through an Ethernet cable Use together with a PoE splitter for a network video product without built-in PoE support	Sustainability	PVC free
Data rate	10/100/1000 Mbps	Display and indicators	LEDs are located on the front panel PoE LED Power LED
Installation and management	Automatically detects PoE and High PoE-enabled devices and supplies inline power Local LED management display	Mounting	Wall, shelf or DIN rail <sup>b</sup> Can be mounted inside AXIS Wall Mount or an equivalent product
Data & power		Operating conditions	<b>Up to 30 W:</b> -10 °C to 55 °C (14 °F to 131 °F) <b>Up to 60 W:</b> -10 °C to 45 °C (14 °F to 113 °F) <b>When mounted inside AXIS T91G61 and connected to an outdoor PTZ:</b> -50 °C to 50 °C (-58 °F to 122 °F) Humidity max 90% RH (non-condensing)
Power	IEEE802.3bt Type 3 Class 6 compatible <sup>a</sup> , High Power over Ethernet, max 60 W	Storage conditions	-20 °C to 70 °C (-4 °F to 158 °F) Humidity max 95% RH (non-condensing)
Input	<b>AC input voltage:</b> 100 to 240 V AC <b>AC frequency:</b> 50–60 Hz	Approvals	<b>Safety</b> IEC/EN/UL 60950-1, EN 62368-1, KC, CCC, CB, S-Mark, GS Mark per EN 60950-1 <b>EMC</b> EN 55032 Class A, EN 61000 3-2, EN 61000 3-3, EN 55035, FCC Part 15 Subpart B Class A, VCCI Class A, RCM AS/NZS CISPR32 Class A, KCC KN32 Class A, KN35, EN 61000-6-1, EN 61000-6-2, EN 50121-4, IEC 62236-4
Output	55 V DC (max 60 W)	Dimensions	50 x 80 x 184 mm (2.0 x 3.1 x 7.2 in)
Connectors	Shielded RJ45, EIA 568A and 568B SFP slot Power connector C14	Weight	517 g (1.1 lb)
Wiring	Data provided over pairs 1/2 and 3/6 for 10/100 Ethernet, over all four pairs for Gigabit Ethernet Power over pairs 1/2 (-), 3/6 (+), 4/5 (+) and 7/8 (-)	Included accessories	Installation guide
		Optional accessories	AXIS T91A03 DIN Rail Clip Mains Cable Angle C13-Open 0.5 m AXIS T8611 SFP Module LC.LX AXIS T8612 SFP Module LC.SX AXIS T8613 SFP Module 1000BASE-T For more accessories, see <a href="http://axis.com">axis.com</a>
		Warranty	3-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>

a. Only applicable for 2675396  
b. Sold as optional accessory