



- Extend an 8K 60Hz HDMI signal up to 33ft (10m)

## Features

- **HDMI SIGNAL BOOSTER:** Combine two standard-length HDMI cables into an extra-long cable supporting up to 8K 60Hz / 4K 144Hz at a max total cable length of 33ft (10m), with 13ft (4m) from source to repeater, and 20ft (6m) from repeater to display
- **COMPACT AND DURABLE:** Lightweight HDMI signal amplifier features a metal housing and a small form factor, making it versatile for installation in a variety of environments; It is ideal for office, education, and digital signage applications
- **FLEXIBLE POWER AND EXTENSION:** TAA Compliant HDMI booster is powered through an available USB Port or USB Wall Charger; 5ft (1.5m) USB-A Cable included; Supports lower resolutions and refresh rates at greater distances such as 1080p at 150ft (45m)
- **UNIVERSAL COMPATIBILITY:** Inline HDMI Repeater requires no drivers or software and works with any operating system, including Windows, macOS, and ChromeOS; It supports active HDMI cables and video adapters, providing versatile functionality
- **TECHNICAL SPECIFICATIONS:** HDMI Extender is HDMI 2.1 compliant, supporting CEC, variable refresh rate, auto low-latency mode, HDR10, HDCP 1.4/2.2/2.3, DSC 1.1/1.2a, and 7.1ch HDMI audio; 48Gbps Bandwidth; 4:4:4 Chroma subsampling; ARC/eARC not supported

---

### Hardware

Warranty	2 Years
Ports	1
Cabling	HDMI
Audio	Yes
Rack-Mountable	No
Daisy-Chain	No

---

### Performance

Maximum Data Transfer Rate	48Gbps
Max Distance	10 m / 33 ft
Maximum Digital Resolutions	7680 x 4320 60Hz
Supported Resolutions	7680 x 4320 60Hz 7680 x 4320 30Hz



3840 x 2160 144Hz

3840 x 2160 120Hz

3840 x 2160 60Hz

5120x1440 60Hz

3440x1400 60Hz

3440x1400 60Hz

2560x1080 75Hz

1920 x 1080 60Hz

<i>Other resolutions and refresh rates may be supported</i>

Wide Screen Supported Yes

Audio Specifications HDMI - 7.1 Channel Audio

**Connector(s)**

Connector Type(s) 1 - HDMI  
 1 - HDMI

**Software**

OS Compatibility No Drivers or Software Required

**Special Notes / Requirements**

Note USB power is not required for most applications  
 Both the source and display must support 8K 60Hz resolution to achieve this resolution  
 ARC/eARC is not supported

**Indicators**

LED Indicators 1 - Solid Green: Powered On

**Power**

Power Source USB-Powered

**Environmental**

Operating Temperature 0C to 40C (32F to 104F)



Storage Temperature	-10C to 60C (14F to 140F)
Humidity	0% ~ 80% RH

---

**Physical Characteristics**

Color	Black
Material	Metal
Product Length	1.9 in [4.9 cm]
Product Width	1.8 in [4.6 cm]
Product Height	0.6 in [1.6 cm]
Weight of Product	2.0 oz [57.0 g]

---

**Packaging Information**

Package Length	5.6 in [14.3 cm]
Package Width	6.6 in [16.8 cm]
Package Height	2.5 in [6.3 cm]
Shipping (Package) Weight	2.1 oz [60.0 g]

---

**What's in the Box**

Included in Package	1 - HDMI Booster
	1 - USB Power Cable
	1 - Quick-Start Guide

---

***\*Product appearance and specifications are subject to change without notice.***

