



[Product Website](#)

## 21" office monitor

The FlexScan S2134 has a screen diagonal of 21 inches in 4:3 format. It convinces with its IPS LCD and the up to 500 cd/sqm bright and economical LED backlight. Its typical power consumption is just 13 watts. Thanks to the Auto EcoView function, the monitor saves additional energy by intelligently adjusting the image brightness to its surroundings. The EcoView Optimizer adjusts the backlight depending on the image content and thus also reduces power consumption. The S2134 stands for maximum user comfort, reduced environmental impact and low operating costs.

4:3 format and IPS panel in compact and space-saving design

Brightness 500 cd/sqm, contrast 1800:1, 178° viewing angle

6 ms switching time gray-gray with overdrive function

Auto EcoView, EcoView Index and EcoView Optimizer for maximum energy savings and optimal ergonomics

USB hub with one upstream and two downstream ports

Display Port, DVI-D and D-Sub input for digital and

Analog connection

5-year warranty for highest investment security

## Technical Data

GENERAL		FEATURES & OPERATION	
Item no.	S2134-BK S2134-GY	Preset color/greyscale modes	2x manual memory locations, sRGB, Paper, Movie, DICOM
Case color	Black Light gray	DICOM tone curve	
Areas of application	Office	Auto EcoView	
Product line	FlexScan	EcoView Index	
Areas of application	Large and medium-sized companies, Private user & small business, Finance	EcoView Optimizer	
Specific system requirements	None, compatible with most computers and operating systems including macOS and Windows	Overdrive	
EAN	4995047065500 4995047065494	No flickering	
		HDCP Decoder	
		Automatic signal input recognition	
		On-screen menu languages	de, en, fr, es, it, se
		Adjustment options	Color Mode, Brightness, Contrast, Color temperature /White point, Gamma, Overdrive, Colour tone, Color saturation, Resolution, Scaling, OSD language, Signal input, All EcoView functions
		Integrated power unit	
SCREEN		ELECTRICAL DATA	
Screen size [in inches]	21,3	Frequency	Digital: 31 - 76 kHz / 59 - 61 Hz; Analog: 24 - 80 kHz / 49 - 76 Hz (1600 x 1200: 59 - 61 Hz)
Screen size [in cm]	54	Power consumption (typical) [in watts]	13
Format	4:3	Maximum Power Consumption [in watts]	42 (at maximum brightness with all signal inputs and USB ports in use)
Viewable image size (width x height) [in mm]	432 x 324	Max. Power consumption in stand-by mode [in watts]	0.5
Ideal and recommended resolution	1600 x 1200	Power consumption with power switch off [in watts]	0
Pixel pitch [in mm]	0,27 x 0,27	Energy efficiency class	C
Pixel density [in ppi]	94	Energy consumption/1000h [in kWh]	10
Supported resolutions	1600 x 1200, 1280 x 1024, 1024 x 768, 800 x 600, 720 x 400, 640 x 480	Power supply	AC 100-240V, 50/60Hz
Panel technology	IPS	Power management	
Max. viewing angle horizontal	178		
Max. viewing angle vertical	178		
Number of colors or greyscale	16.7 million colors (D-Sub, 8 Bit), 16.7 million colors (DVI, 8 Bit), 16.7 million colors (DisplayPort, 8 Bit)		
Color palette/look-up table	1.06 billion color tones / 10 Bit		
Max. color space (typical)	sRGB		
Max. brightness (typical) [in cd/m ]	500		
Max. dark room contrast (typical)	1800:1		
Response time grey-grey alternation (typical) [in ms]	6		
Backlight	LED		
CONNECTIONS		DIMENSIONS & WEIGHT	
Signal inputs	D-Sub, DisplayPort (HDCP 1.3), DVI-D (HDCP 1.4)	Dimensions (incl. stand) (width x height x depth) [in mm]	465 x 453 - 535 x 208.5
USB specification	USB 2	Weight (incl. stand) [in kg]	8.1
USB upstream ports	1 x type B	Dimensions (without stand) (width x height x depth) [in mm]	465 x 361 x 64
USB downstream ports	2x type A	Weight (without stand) [in kg]	5.1
Graphic signal	DVI Single Link (TMDS), RGB Analog, DisplayPort	Dimension drawing (PDF)	<a href="#">Dimension drawing (PDF)</a>
Sync formats	Separate	Rotatability of the stand [in °]	70
		Tiltability forwards/backwards [in °]	0 / 40
		Pivot between portrait / landscape	clockwise
		Height adjustment range [in mm]	82
		Hole spacing	100 x 100



# FlexScan S2134

## CERTIFICATION & STANDARDS

Certification	CE, UKCA, CB, TÜV/GS, TÜV/Ergonomics (including ISO 9241-307), RCM, cTÜVus, FCC-B, CAN ICES-3 (B), TÜV/S, VCCI-B, EPA ENERGY STAR, RoHS, WEEE, China RoHS, CCC
---------------	--

## SOFTWARE & ACCESSORIES

Other box contents	Signal cable D-Sub - D-Sub, Signal cable DVI-D - DVI-D, USB cable (Type A - Type B), Manual via download, Power cord, Quick guide
--------------------	---

Accessories	PM200-K, CP200, PP100-K, PP200-K
-------------	----------------------------------

## WARRANTY

Warranty periode	5 years for unit and LCD module up to 30,000 operating hours, whichever comes first.
------------------	--

Find your EIZO contact:  
EIZO Europe GmbH  
Belgrader Straße 2  
41069 Mönchengladbach  
Phone: +49 2161 8210-0  
[www.eizo.eu](http://www.eizo.eu)

All product names are trademarks or registered trademarks of EIZO Corporation in Japan and other countries or their respective companies. Copyright © 2024 EIZO Europe GmbH, Belgrader Str. 2, 41069 Mönchengladbach, Germany. All rights, errors and modifications reserved. Latest update: 16.07.2024