

GIGABYTE B760M H DDR4 Motherboard - Supports Intel Core 14th Gen CPUs, 6+1+1 Phases Digital VRM, up to 3200MHz DDR4 (OC), 2xPCIe 4.0 M.2, GbE LAN, USB 3.2 Gen1

Brand : GIGABYTE

Product code: B760M H DDR4

Product name : B760M H DDR4 Motherboard - Supports Intel Core 14th Gen CPUs, 6+1+1 Phases Digital VRM, up to 3200MHz DDR4 (OC), 2xPCIe 4.0 M.2, GbE LAN, USB 3.2 Gen1

- Intel® Socket LGA 1700 []Support 13th and 12th Gen Series Processors
- Unparalleled Performance[]Hybrid 6+1+1 Phases Digital VRM Solution
- Dual Channel DDR4[]2*DIMMs XMP Memory Module Support
- Next Generation Storage[]2*PCIe 4.0 x4 M.2 Connectors
- EZ-Latch \Box PCIe 4.0x16 Slot with Quick Release Design
- Fast Networks GbE LAN
- Extended Connectivity []HDMI, D-Sub

- Smart Fan 6 Features Multiple Temperature Sensors, Hybrid Fan Headers with FAN STOP

B760M H DDR4 Intel LGA 1700 m-ATX Motherboard, 4x DDR4 ~128GB, 2x PCI-E x16, 2x M.2, 4x SATA, 3x USB 3.2, 2x USB 2.0, 1x Type-C

GIGABYTE B760M H DDR4 Motherboard - Supports Intel Core 14th Gen CPUs, 6+1+1 Phases Digital VRM, up to 3200MHz DDR4 (OC), 2xPCIe 4.0 M.2, GbE LAN, USB 3.2 Gen1:

Elevate your computing experience with GIGABYTE's renowned motherboard series: AORUS, AERO, and GIGABYTE. Featuring innovative designs and advanced features, these boards offer exceptional performance and reliability. Whether you're a gamer, content creator, or professional, our series cater to your needs, ensuring uncompromising quality and cutting-edge technology.






Processor		Rear panel I/O ports	
Processor manufacturer * Processor socket * Compatible processor series *	Intel LGA 1700 Intel® Celeron®, Intel® Pentium® Gold	VGA (D-Sub) ports quantity * HDMI ports quantity * HDMI version DisplayPorts quantity	1 1 1.4 1
Maximum number of SMP processors	1	DisplayPort version	1.4
Supported processor sockets	LGA 1700	Network	
Maximum internal memory supported by processor	64 GB	Ethernet LAN Ethernet interface type	✔ Gigabit Ethernet
Memory		Wi-Fi *	×
Supported memory types *	DDR4-SDRAM	Features	
Number of memory slots * Memory slots type Memory channels ECC compatibility Non-ECC Supported memory clock speeds Supported memory clock speed (max) Maximum internal memory * Supported memory module capacities	2 DIMM Dual-channel Non-ECC ✓ 2133,2400,2666,2933,3000,3200 MHz 3200 MHz 64 GB 1GB, 2GB, 4GB, 8GB, 12GB, 16GB, 32GB	Motherboard chipset * Audio chip Audio output channels * Product colour Component for * Motherboard form factor * Motherboard chipset family * Power source type Windows operating systems supported Expansion slots	Intel B760 Express Realtek ALC897 7.1 channels Brown PC micro ATX Intel ATX Windows 10, Windows 11
Storage controllers		PCI Express x16 (Gen 4.x) slots	1
Supported storage drive interfaces * Number of HDDs supported Number of storage drives supported RAID support RAID levels	4	Number of M.2 (M) slots BIOS BIOS type * BIOS memory size ACPI version	2 UEFI AMI 128 Mbit 5.0
Graphics		Clear CMOS jumper	4
		Desktop Management Interface (DMI) version	2.7

Graphics		BIOS	
Parallel processing technology support *	Not supported	System Management BIOS (SMBIOS) version	2.7
DirectX version	12.1	Logistics data	
Internal I/O		Country of origin	China
USB 2.0 connectors *	2	Products per shipping (inner) case	1 pc(s)
USB 3.2 Gen 1 (3.1 Gen 1) connectors *	1	Battery	
Number of SATA III connectors *	4	Battery weight	3 g
Total number of SATA connectors	4	Lithium weight per battery	0.07 g
Front panel audio connector	1	Number of battery cells	1
Front panel connector	<	Battery technology	Lithium-Manganese Dioxide (LiMnO2)
ATX Power connector (24-pin)	✓	Battery type	CR2032
CPU fan connector	✓		
EPS power connector (8-pin)	✓	Packaging data	
TPM connector	✓	Package width	265 mm
Serial port headers	1	Package depth	265 mm
RGB LED pin header	✓	Package height	54 mm
Rear panel I/O ports		Package weight	825 g
USB 2.0 ports quantity *	2	Weight & dimensions	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A	4	Width	230 mm
ports quantity *		Depth	215 mm
Ethernet LAN (RJ-45) ports *	1	Height	35 mm
		Packaging content	
		Batteries included	<
		Technical details	

Warranty period

3 year(s)



4719331854645

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.