

GIGABYTE H510M S2H V3 Motherboard - Supports Intel Core 11th CPUs, up to 3200MHz DDR4 (OC), 1xPCle 3.0 M.2, GbE LAN, USB 3.2 Gen 1

Brand: GIGABYTE Product code: H510M S2H V3

Product name: H510M S2H V3 Motherboard - Supports Intel Core 11th CPUs, up to 3200MHz DDR4 (OC), 1xPCle 3.0 M.2,

GbE LAN, USB 3.2 Gen 1

- Supports 11th/10th Gen Intel® Core $^{\scriptscriptstyle\mathsf{TM}}$ Processors
- Dual Channel Non-ECC Unbuffered DDR4, 2 DIMMs
- 8-Channel HD Audio with High Quality Audio Capacitors
- NVMe PCIe Gen3 x4 2280 M.2 Connector
- GbE LAN with Bandwidth Management
- Smart Fan 5 features Multiple Temperature Sensors and Hybrid Fan Headers with FAN STOP
- GIGABYTE APP Center, Simple and Easy Use
- Anti-Sulfur Resistors Design

LGA1200, Intel H470, 2 x DDR4, 3200 MHz, 1 x DisplayPort, 1 x HDMI port, 1 x D-Sub, Micro ATX

GIGABYTE H510M S2H V3 Motherboard - Supports Intel Core 11th CPUs, up to 3200MHz DDR4 (OC), 1xPCle 3.0 M.2, GbE LAN, USB 3.2 Gen 1:

Elevate your computing experience with GIGABYTE's renowned motherboard series: AORUS, AERO, and GIGABYTE. Featuring innovative designs and advanced features, these boards offer exceptional performance and reliability. Whether you're a gamer, content creator, or professional, our series cater to your needs, ensuring uncompromising quality and cutting-edge technology.





Processor		Rear panel I/O ports	
Processor manufacturer * Processor socket * Compatible processor series * Supported processor sockets Maximum internal memory supported by processor	Intel LGA 1200 (Socket H5) Intel® Celeron®, Intel® Core™ i3, Intel® Core™ i5, Intel® Core™ i7, Intel® Core™ i9, Intel® Pentium® LGA 1200 (Socket H5)	PS/2 ports quantity VGA (D-Sub) ports quantity * HDMI ports quantity * DisplayPorts quantity DisplayPort version Microphone in USB connector type	2 1 1 1 1.2 ✓ USB Type-A
Memory		Network	
Supported memory types * Number of memory slots * Memory slots type	DDR4-SDRAM 2 DIMM	Ethernet LAN Ethernet interface type Wi-Fi *	✓ Gigabit Ethernet
Memory channels	Dual-channel	Features	
ECC compatibility Supported memory clock speeds Supported memory clock speed (max) Maximum internal memory * Supported memory module capacities	ECC & Non-ECC 2133,2400,2666,2933,3000,3200 MHz 3200 MHz 64 GB 1GB, 2GB, 4GB, 8GB, 12GB, 16GB, 32GB	Motherboard chipset * Audio output channels * Product colour PC health monitoring Component for * Motherboard form factor * Motherboard chipset family *	Intel H470 Express 7.1 channels Brown Fan, Temperature, Voltage PC micro ATX Intel
Unbuffered memory	✓	Windows operating systems	Windows 10 x64, Windows 11 x64
Storage controllers		supported	Wildens 10 Ad I, Wildens 11 Ad I
Supported storage drive types Supported storage drive interfaces * Number of HDDs supported Number of storage drives supported	4	Expansion slots PCI Express x1 slots PCI Express x16 slots Number of M.2 (M) slots	2 1 1
Graphics		BIOS	
Parallel processing technology support * Maximum resolution HDCP	Not supported 4096 x 2304 pixels ✓	BIOS type * BIOS memory size ACPI version Clear CMOS jumper	UEFI AMI 128 Mbit 5.0 ✓

Graphics		BIOS	
DirectX version Number of displays supported	12.0 2	Desktop Management Interface (DMI) version	2.7
Internal I/O	-	System Management BIOS (SMBIOS) version	2.7
USB 2.0 connectors * USB 3.2 Gen 1 (3.1 Gen 1) connectors *	1	Logistics data	
	1	Country of origin	China
Number of SATA III connectors *	4	Products per shipping (inner) case	1 pc(s)
Total number of SATA connectors	4	Battery	
Front panel audio connector	✓	Battery weight	3 g
Front panel connector	✓	Lithium weight per battery	0.07 g
ATX Power connector (24-pin)	✓	Number of battery cells	1
CPU fan connector Number of chassis fan connectors EPS power connector (8-pin) TPM connector	2 √	Battery technology	Lithium-Manganese Dioxide (LiMnO2)
		Battery type	CR2032
		Packaging data	
Serial port headers	1	Package width	265 mm
12V power connector	✓	Package depth	235 mm
RGB LED pin header	✓	Package height	52 mm
Rear panel I/O ports		Package weight	760 g
USB 2.0 ports quantity *	4	Weight & dimensions	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity *	2	Width	226 mm
Ethernet LAN (RJ-45) ports *	1	Depth	185 mm
Ethernet Eniv (NJ-43) ports	1	Height	35 mm
		Packaging content	
		Cables included	SATA
		Batteries included	✓
		Drivers included	✓
		Technical details	
		Warranty period	3 year(s)



4719331855420

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.