



Lindy 5m USB 3.2 Gen 1 C/A Active Extension Pro

Brand : Lindy

Product code: 43380

Product name : 5m USB 3.2 Gen 1 C/A Active Extension Pro

- High performance, active cable that provides an extended 5m connection between a computer with USB Type C port and a USB Type A device
- Can be used standalone or as part of the Lindy Active Extension System Pro to create bespoke extension systems of over 40m (depending on the cables used)
- Supports the full USB 3.2 / 3.1 Gen 1 / USB 3.0 SuperSpeed bandwidth for speeds of 5Gbps
- USB Power Adapter cable included
- 2 year warranty

5m USB 3.2 Gen 1 C/A Active Extension Pro

Lindy 5m USB 3.2 Gen 1 C/A Active Extension Pro. Cable length: 5 m. Connector 1: USB C, Connector 2: USB A, USB version: USB 3.2 Gen 1 (3.1 Gen 1), Connector contacts plating: Gold, Product colour: Black



Features		Weight & dimensions	
USB version *	USB 3.2 Gen 1 (3.1 Gen 1)	Cable length *	5 m
Connector 1 *	USB C	Cable diameter	5 mm
Connector 2 *	USB A	Weight	220 g
Connector 1 gender *	Male	Bend radius (min)	5.5 cm
Connector 2 gender *	Female	Connector 1 dimensions (WxDxH)	12.4 x 39.7 x 9 mm
Connector 1 form factor	Straight	Connector 2 dimensions (WxDxH)	20 x 80 x 13 mm
Connector 2 form factor	Straight	Packaging data	
AWG wire size	28/28/24	Package type	Carton
Connector material	Nickel	Package width	230 mm
Contact material	Brass	Package depth	198 mm
Connector contacts plating	Gold	Package height	63 mm
Cable jacket material	Polyvinyl chloride (PVC)	Package weight	420 g
Conductor material	Tinned copper	Packaging content	
Connector shielding	✓	Quantity per pack *	1 pc(s)
Connector shield material	Aluminium	Manual	✓
Connector housing material	Plastic	Sustainability	
Product colour *	Black	Sustainability compliance	✓
Cable type	Round cable	Operational conditions	
Transmission medium	Twisted pair	Operating temperature (T-T)	0 - 50 °C
Nominal attenuation	0.064MHz - <0.08dB	Storage temperature (T-T)	-20 - 60 °C
	0.256MHz - <0.13dB	Other features	
	0.512MHz - <0.15dB	Warranty period	2 year(s)
	0.772MHz - <0.15dB	Compliance certificates	CE, Federal Communications Commission (FCC), REACH, RoHS
	1.0MHz - <0.20dB		
	4MHz - <0.39dB		
Certification	<0.57dB		
	12MHz - <0.67dB		
	24MHz - <0.95dB		
	48MHz - <1.35dB		
Power	<1.90dB		
	200MHz - <3.20dB		
Power note	2.5/0.7mm DC		



4002888433808

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 31-OCT-2024. Prints or copies of Information are only valid on the printed Publication date