



## DeepCool PX850G power supply unit 850 W 20+4 pin ATX ATX Black

**Brand :** DeepCool

**Product code:** R-PX850G-FC0B-UK

**Product name :** PX850G

850 W, 80 Plus GOLD, 135 mm, ATX12V V3.0, 150 × 160 × 86 mm

DeepCool PX850G. Total power: 850 W, AC input voltage: 100 - 240 V, Maximum input current (@110V): 5 A. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 60 cm, SATA power cable length: 500,650,800,950 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 13.5 cm. Cables included: AC, PCIe, CPU, Peripheral (Molex), SATA



| Power   |   | Ports & interfaces                    |   |
|---|---|---------------------------------------|---|
| Total power *                                 | 850 W   | CPU power connector (4+4 pin)         | ✓                                       |
| AC input voltage *                            | 100 - 240 V   | CPU power cable length                | 70 cm                                   |
| Maximum input current (@110V)                 | 5 A   | ATX power connector (20+4 pin)        | ✓                                       |
| Maximum input current (@220V)                 | 10 A  | PCI Express connector                 | ✓                                       |
| Power Factor Correction (PFC) type            | Active  | Cabling type                          | Fully-Modular                           |
| Combined power (+3.3V)                        | 120 W   | Performance                           |   |
| Combined power (+12V)                         | 849.6 W   | 80 PLUS certification *               | 80 PLUS Gold                            |
| Combined power (+5V)                          | 120 W   | Purpose *                             | PC                                      |
| Combined power (-12V)                         | 3.6 W   | Power supply unit (PSU) form factor * | ATX                                     |
| Combined power (+5Vsb)                        | 15 W  | ATX version                           | 3.0                                     |
| Max output current (+3.3V)                    | 22 A  | Bearing technology                    | FDB                                     |
| Max output current (+12V)                     | 70.8 A  | Mean time between failures (MTBF)     | 100000 h                                |
| Max output current (+5V)                      | 22 A  | Certification                         | Cybenetics Gold                         |
| Max output current (-12V)                     | 0.3 A   | Design                                |   |
| Max output current (+5Vsb)                    | 3 A   | Product colour                        | Black                                   |
| Hold time                                     | 16 ms   | Cooling type                          | Active                                  |
| Efficiency                                    | 90%   | Fan diameter                          | 13.5 cm                                 |
| Power protection features                     | Over current, Over power, Over voltage, Overheating, Short circuit, Under power | Number of fans                        | 1 fan(s)                                |
| Ports & interfaces                            |   | Fan location                          | Top                                     |
| Motherboard power connector *                 | 20+4 pin ATX  | On/off switch                         | ✓                                       |
| Motherboard power cable length                | 60 cm   | Operational conditions                |   |
| Number of SATA power connectors               | 8   | Operating temperature (T-T)           | 0 - 40 °C                               |
| SATA power cable length                       | 500,650,800,950 mm  | Packaging content                     |   |
| Peripheral (Molex) power connectors (4-pin) * | 4   | Cables included                       | AC, PCIe, CPU, Peripheral (Molex), SATA |

| Ports & interfaces                     |                    | Weight & dimensions       |  |
|--|--------------------|---------------------------|--|
| Peripheral (Molex) power cable length  | 500,650,800,950 mm | Width                     | 150 mm   |
| PCI Express power connectors (6+2 pin) | 3                  | Depth                     | 160 mm   |
| PCI Express power connectors (16-pin)  | 1                  | Height                    | 86 mm  |
| PCI Express power cable length         | 65 cm              | <b>Packaging data</b>     |  |
|  |                    | Package type              | Box  |
|  |                    | <b>Technical details</b>  |  |
|  |                    | Sustainability compliance | ✓  |
|  |                    | Warranty period           | 10 year(s)   |
|  |                    | Compliance certificates   | CE, EAC, Federal Communications Commission (FCC), UKCA |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 31-OCT-2024. Prints or copies of Information are only valid on the printed Publication date