



DeepCool PX1200G power supply unit 1200 W 20+4 pin ATX ATX Black

Brand : DeepCool

Product code: R-PXC00G-FC0B-UK

Product name : PX1200G

1200 W, 80 Plus GOLD, ATX12V V3.0, 150 × 160 × 86 mm

DeepCool PX1200G. Total power: 1200 W, AC input voltage: 100 - 240 V, Maximum input current (@110V): 15 A. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 60 cm, SATA power cable length: 500,650,800,950 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 13.5 cm. Cables included: AC, PCIe, CPU, Peripheral (Molex), SATA



Power		Ports & interfaces	
Total power *	1200 W	PCI Express power cable length	65 cm
AC input voltage *	100 - 240 V	CPU power connector (4+4 pin)	✓
Maximum input current (@110V)	15 A	CPU power cable length	70 cm
Maximum input current (@220V)	7.5 A	ATX power connector (20+4 pin)	✓
Power Factor Correction (PFC) type	Active	PCI Express connector	✓
Combined power (+3.3V)	120 W	Cabling type	Fully-Modular
Combined power (+12V)	1200 W	Performance	
Combined power (+5V)	120 W	80 PLUS certification *	80 PLUS Gold
Combined power (-12V)	3.6 W	Purpose *	PC
Combined power (+5Vsb)	15 W	Power supply unit (PSU) form factor *	ATX
Max output current (+3.3V)	2 A	ATX version	3.0
Max output current (+12V)	100 A	Bearing technology	FDB
Max output current (+5V)	22 A	Mean time between failures (MTBF)	100000 h
Max output current (-12V)	0.3 A	Certification	Cybenetics Platinum
Max output current (+5Vsb)	3 A	Design	
Hold time	16 ms	Product colour	Black
Efficiency	90%	Cooling type	Active
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage	Fan diameter	13.5 cm
Ports & interfaces		Number of fans	1 fan(s)
Motherboard power connector *	20+4 pin ATX	Fan location	Top
Motherboard power cable length	60 cm	On/off switch	✓
Number of SATA power connectors	8	Operational conditions	
SATA power cable length	500,650,800,950 mm	Operating temperature (T-T)	0 - 40 °C
Peripheral (Molex) power connectors (4-pin) *	4		

Ports & interfaces		Packaging content	
Peripheral (Molex) power cable length	500,650,800,950 mm	Cables included	AC, PCIe, CPU, Peripheral (Molex), SATA
PCI Express power connectors (6+2 pin)	3	Weight & dimensions	
PCI Express power connectors (16-pin)	1	Width	150 mm
		Depth	160 mm
		Height	86 mm
		Packaging data	
		Package type	Box
		Technical details	
		Sustainability compliance	✓
		Compliance certificates	CCC, CE, EAC, Federal Communications Commission (FCC)

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 31-OCT-2024. Prints or copies of Information are only valid on the printed Publication date