

ZH350ST

Ultra-compact high brightness Full HD 1080p laser projector









- Bright Full HD 1080p DuraCore laser projector -3500 lumens and IP6X certified
- Ultra compact and short throw lens for easy installation - 360-degree and portrait projection
- DuraCore laser technology 30,000 hours maintenance-free laser light source
- Designed with the environment in mind -DuraCore laser technology cuts power consumption and ensures a long product lifespan



The ZH350ST is one of Optoma's most compact, hassle free Full HD 1080p DuraCore laser projectors to date. This 3500-lumen projector is built for maintenance-free continuous operation up to 30,000 hours, while its small and lightweight footprint makes it smaller than the previous generation, offering flexible installation in virtually any orientation and location.

Designed with the environment in mind, the ZH350ST cuts power consumption compared to a typical lamp-based Optoma projector. In addition, laser technology maintains brightness and colour saturation for longer, ensuring excellent image quality and a long product lifespan without the need for routine lamp changes.

Specifications

EAN: 5055387666795, Colour: White

UPC: 796435 44 657 4, Colour: White

Display/image

Display technology DLP™

Resolution 1080p Full HD (1920x1080)

 Brightness
 3,500 lumens

 Contrast ratio
 300,000:1

 Native aspect ratio
 16:9

 Aspect ratio - compatible
 4:3,16:9,16:10

 Keystone correction +/-30°

horizontal

Keystone correction - vertical +/-30° **Has vertical auto keystone** Yes

correction Yes

Screen size 0.76m ~ 7.62m (30" ~ 300") diagonal

Lamp info

Laser
LASER life Laser
30,000 hours

Optical Throw ratio

 Throw ratio
 0.496:1

 Projection distance (m)
 0.3m - 3.3m

 Zoom type
 Manual

 Focal length (mm)
 7.51

 Native offset
 116%

Connectivity

Connections Inputs 2 x HDMI 2.0

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A

Control 1 x RS232

General

Noise level (typical) 32dB Noise level (max) 34dB

PC compatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p,

720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)

3D compatibility Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D)

720p50 / 60

3D ready

Security bar, Kensington Lock, Password protected interface

IP rating IP6X

OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese

24/7 operation Yes

360° operation Yes

Operating conditions 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m

 Remote control
 Card style

 Speaker count
 1

 Watts per speaker
 15W

In the box AC power cord Remote control

2x AAA batteries Basic user manual

 Input lag
 8.60ms

 Optional wireless models
 UHDCast Pro

Power

Power supply 100V ~ 240V, 50-60Hz

 Power consumption (standby)
 <0.5W</td>

 Power consumption (min)
 98W

 Power consumption (max)
 139W

Weight and dimensions

 Dimensions (W x D x H) mm
 274 x 216 x 114

 Gross weight
 4.2 kg

 Net weight
 3 kg





