



# Next-generation Gateway Pro

Dual-WAN security gateway designed to protect medium to large-sized networks with enterprise-class firewall configuration and threat management features.

The UniFi Next-generation Gateway Pro (UXG Pro) is a powerful security gateway that delivers a versatile networking interface and enterprise-class threat management functionality to medium to large-sized networks. The UXG Pro is equipped with (2) WAN ports (GbE RJ45 and 10G SFP+) that provide failover support, as well as (2) LAN ports (GbE RJ45 and 10G SFP+) to provide the high-speed connectivity needed to support the most bandwidth-intensive applications. It also excels as a complete network security solution, offering a full suite of threat mitigation features, including deep packet inspection (DPI), intrusion detection and prevention systems (IDS/IPS), and layered firewall configuration. The UXG Pro can be paired with a Cloud Key Gen2 Plus to create a highly powerful and secure deployment that can be fully managed with the UniFi Network application.



## Mechanical

Dimensions	442.4 x 43.7 x 285.6 mm (17.42 x 1.72 x 11.24")
Weight	3.42 kg (7.54 lb)
Enclosure materials	Front panel: aluminum CNC Top cover/base: SGCC steel

## Hardware

Processor	Quad-core ARM® Cortex®-A57 at 1.7 GHz				
Memory information	2 GB DDR4				
Management interface	Ethernet				
Networking interface	LAN: (1) 1 GbE RJ45 port (1) 10G SFP+ port WAN: (1) 1 GbE RJ45 port (1) 10G SFP+ port				
LCM display	(1) 1.3" touchscreen Bootup animation: bootup in progress Firmware upgrade icon: firmware upgrading				
Button	Factory reset				
Power method	<table border="1"><tr><td>US</td><td>(1) Universal AC input, 125VAC, 2.7A max., 60 Hz (1) RPS DC input, 11.5VDC, 2.87A</td></tr><tr><td>Worldwide</td><td>(1) Universal AC input, 200-240VAC, 1.7A max., 50/60 Hz (1) RPS DC input, 11.5VDC, 2.87A</td></tr></table>	US	(1) Universal AC input, 125VAC, 2.7A max., 60 Hz (1) RPS DC input, 11.5VDC, 2.87A	Worldwide	(1) Universal AC input, 200-240VAC, 1.7A max., 50/60 Hz (1) RPS DC input, 11.5VDC, 2.87A
US	(1) Universal AC input, 125VAC, 2.7A max., 60 Hz (1) RPS DC input, 11.5VDC, 2.87A				
Worldwide	(1) Universal AC input, 200-240VAC, 1.7A max., 50/60 Hz (1) RPS DC input, 11.5VDC, 2.87A				
Power supply	AC/DC, internal, 50W				
Max. power consumption	30W				
ESD/EMP protection	Air: ± 15 kV, contact: ± 8 kV				
Operating temperature	-10 to 40° C (14 to 104° F)				
Operating humidity	5 - 95% noncondensing				
Certifications	CE, FCC, IC				

## LEDs

AC outlet/ RPS	Blue
Ethernet	Green/amber
SFP+	White/green



Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at [www.ui.com/support/warranty](http://www.ui.com/support/warranty)

©2022 Ubiquiti Inc. All rights reserved. Ubiquiti, Ubiquiti Networks, the Ubiquiti U logo, the Ubiquiti beam logo, UniFi, and UniFi Network are trademarks or registered trademarks of Ubiquiti Inc. in the United States and in other countries. Arm and Cortex are registered trademarks of Arm Limited (or its subsidiaries) in the US and/or elsewhere. All other trademarks are the property of their respective owners.