Philips 6000 series 45B1U6900C/00 LED display 113 cm (44.5") 5120 x 1440 pixels UltraWide Dual Quad HD Black

Brand : Philips   **Product family:** 6000 series   **Product code:** 45B1U6900C/00

Product name :
45B1U6900C/00

Curved Business Monitor 45B1U6900C 32:9 SuperWide curved monitor with USB-C

Philips 6000 series 45B1U6900C/00 LED display 113 cm (44.5") 5120 x 1440 pixels UltraWide Dual Quad HD Black:

This Philips USB-C multi-purpose monitor offers clutter-free setup. With a single cable you can view smooth, high-resolution video, transfer data and charge your laptop. The headphone holder brings cable management to the next level.
Philips 6000 series 45B1U6900C/00. Display diagonal: 113 cm (44.5"), Display resolution: 5120 x 1440 pixels, HD type: UltraWide Dual Quad HD, Display technology: LED, Response time: 4 ms, Native aspect ratio: 32:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black

Display

Display diagonal *	113 cm (44.5")
Display resolution *	5120 x 1440 pixels
HD type *	UltraWide Dual Quad HD
Native aspect ratio *	32:9
Display technology *	LED
Panel type *	VA
Backlight type	W-LED
Touchscreen *	✘
Display brightness (typical)	450 cd/m²
Response time *	4 ms
Anti-glare screen	✔
Screen shape *	Curved
Screen curvature rating	1500R
Contrast ratio (typical) *	3000:1
Contrast ratio (dynamic)	80000000:1
Dynamic contrast ratio marketing name	SmartContrast
Maximum refresh rate *	75 Hz
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours *	16.7 million colours
Pixel pitch	0.2124 x 0.2124 mm
Pixel density	120 ppi
Horizontal scan range	30 - 114 kHz
Vertical scan range	48 - 75 Hz
Viewable size, horizontal	108.7 cm
Viewable size, vertical	30.6 cm
Display diagonal (metric)	113 cm
High Dynamic Range (HDR) supported	✔

Network

Ethernet LAN	✔

Ergonomics

VESA mounting *	✔
Panel mounting interface	100 x 100 mm
Cable lock slot *	✔
Cable lock slot type	Kensington
Height adjustment *	✔
Height adjustment	15 cm
Swivelling	✔
Swivel angle range	-45 - 45°
Tilt adjustment	✔
Tilt angle range	-5 - 15°
Picture-in-Picture	✔
On Screen Display (OSD)	✔
On Screen Display (OSD) languages	Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian
Number of OSD languages	21
Plug and Play	✔
LED indicators	Operation, Stand-by

Power

Energy efficiency class (SDR) *	G
Power consumption (typical) *	46.3 W
Power consumption (standby) *	0.3 W
Power consumption (PowerSave)	36.5 W
AC input voltage	100 - 240 V

Display

High Dynamic Range (HDR) technology	DisplayHDR 400
DDC/CI	✔
Haze rate	25%
Surface hardness	2H
Colour depth	8 bit
sRGB coverage (typical)	123%
NTSC coverage (typical)	107%
Display sRGB	✔

Performance

VESA Adaptive Sync support	✔
Component video sync	Separate sync
Flicker-free technology	✔

Multimedia

Number of speakers	2
Built-in speaker(s) *	✔
Built-in camera *	✘

Design

Market positioning *	Business
Product colour *	Black
Frameless design	✔
Front bezel colour	Black
Feet colour	Black

Ports & interfaces

Built-in USB hub *	✔
USB hub version	3.2 Gen 1 (3.1 Gen 1)
USB upstream port type	USB Type-B, USB Type-C
Number of upstream ports	2
Number of USB Type-B upstream ports quantity	1
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	4
USB Type-C downstream ports quantity	1
USB Type-C DisplayPort Alternate Mode	✔
USB Power Delivery	✔
USB Power Delivery up to	100 W
HDMI *	✔
HDMI version	2.0
DisplayPorts quantity	1
DisplayPort version	1.4
Audio output	✔
Built-in KVM switch	✔
HDCP	✔
HDCP version	1.4/2.2
AC (power) in	✔

Power

AC input frequency	50 - 60 Hz
Power supply type	Internal

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	20 - 80%
Operating altitude	0 - 3658 m
Non-operating altitude	0 - 12192 m

Weight & dimensions

Width (with stand)	1085 mm
Depth (with stand)	238 mm
Height (with stand)	515 mm
Weight (with stand)	12.8 kg
Width (without stand)	1085 mm
Depth (without stand)	158 mm
Height (without stand)	337 mm
Weight (without stand)	9.75 kg

Packaging data

Package width	1180 mm
Package depth	535 mm
Package height	235 mm
Package weight	17.1 kg

Packaging content

Stand included	✔
Cables included	HDMI, DisplayPort, USB Type-C, AC
Manual	✔
Bundled software	SmartControl

Sustainability

Sustainability certificates	ENERGY STAR, TCO
Doesn't contain	Mercury, PVC/BFR

Other features

HBR3 support	✔
Compatible operating systems	Mac OS X, Windows 11/10/8.1/8
Picture-by-Picture (PbP)	✔
Exterior finish type	Textured
Picture enhancement	SmartImage
Recyclable packaging material	100%
Regulatory Approvals	CB; CE Mark; FCC Class B; ICES-003; CU-EAC; EAEU RoHS; TUV Ergo; TUV/GS; TUV Eyesafe certified; cETLus
Delta E	2
Light sensor	✔
EasyRead mode	✔
LowBlue mode	✔
Philips SmartUniformity	93 - 105%
Compliance certificates	RoHS
Mean time between failures (MTBF)	70000 h
Ethernet LAN data rates	10,100,1000 Mbit/s
Wake-on-LAN	✔

Recycling data

Post-consumer recycled plastic	85%

8712581797454