

Philips 6000 series 45B1U6900CH/75 LED display 113 cm (44.5") 5120 x 1440 pixels UltraWide Dual Quad HD LCD Black

Brand : Philips **Product family:** 6000 series **Product code:** 45B1U6900CH/75

Product name: 45B1U6900CH/75

Curved Business Monitor 45B1U6900CH 32:9 SuperWide curved monitor with USB-C

Philips 6000 series 45B1U6900CH/75 LED display 113 cm (44.5") 5120 x 1440 pixels UltraWide Dual Quad HD LCD Black:

This USB-C monitor is for data transfer, power delivery and watching videos. The integrated 5 MP webcam delivers sharp images, and the noise cancelling mic lets people hear you fine. Windows Hello Webcam for quick access and strong security.

Philips 6000 series 45B1U6900CH/75. Display diagonal: 113 cm (44.5"), Display resolution: 5120 x 1440 pixels, HD type: UltraWide Dual Quad HD, Display technology: LCD, Response time: 4 ms, Native aspect ratio: 32:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 2 (3.1 Gen 2). VESA mounting, Height adjustment. Product colour: Black











	Network	
113 cm (44.5")	Ethernet LAN	✓
5120 x 1440 pixels	Ergonomics	
UltraWide Dual Quad HD 32:9 LCD VA W-LED X 450 cd/m² 4 ms ✓ Curved 1500R 3000:1 80000000:1 SmartContrast 75 Hz 178° 178° 16.7 million colours	VESA mounting * Panel mounting interface Cable lock slot * Cable lock slot type Height adjustment * Height adjustment Swivelling Swivel angle range Tilt angle range Picture-in-Picture On Screen Display (OSD) On Screen Display (OSD) languages Plug and Play LED indicators	✓ 100 x 100 mm ✓ Kensington ✓ 15 cm ✓ -45 - 45° -5 - 15° ✓ ✓ Simplified Chinese, Traditional Chinese, Czech, German, Dutch, English, Spanish, Finnish, French, Greek, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Swedish, Turkish, Ukrainian ✓ Operation, Stand-by
0.2124 x 0.2124 mm	Power	
120 ppi 30 - 114 kHz 48 - 75 Hz 108.7 cm 30.6 cm 113 cm	Energy efficiency class (SDR) * Energy efficiency class (HDR) * Energy consumption (SDR) per 1000 hours * Energy consumption (HDR) per 1000 hours * Power consumption (typical) * Power consumption (standby) *	G G 58 kWh 77 kWh 46.3 W
	5120 x 1440 pixels UltraWide Dual Quad HD 32:9 LCD VA W-LED	113 cm (44.5") 5120 x 1440 pixels UltraWide Dual Quad HD 32:9 LCD VA W-LED W-LED Wasser 4 ms Curved 1500R 3000:1 80000000:1 SmartContrast 75 Hz 178° 16.7 million colours 0.2124 x 0.2124 mm 120 ppi 30- 114 kHz 48 - 75 Hz 108.7 cm 30.6 cm 113 cm Ethernet LAN Ergonomics VESA mounting * Panel mounting interface Cable lock slot * Vesa mounting * Panel mounting interface Cable lock slot * Vesa mounting * Panel mounting interface Cable lock slot * Vesa mounting * Panel mounting interface Cable lock slot * Vesa mounting * Panel mounting interface Cable lock slot * Vesa mounting * Panel mounting interface Cable lock slot * Vesa mounting * Panel mounting interface Cable lock slot * Vesa mounting * Panel mounting interface Cable lock slot * Vesa mounting * Panel mounting interface Cable lock slot * Vesa mounting * Panel mounting interface Cable lock slot * Vesa mounting * Panel mounting interface Cable lock slot * Panel mounting interface Cable lock slot * Peanel mounting interface Cable lock slot * Panel mo

Display		Power	
High Dynamic Range (HDR) technology DDC/CI Haze rate Surface hardness Colour depth	DisplayHDR 400 ✓ 25% 2H 8 bit	Power consumption (PowerSave) AC input voltage AC input frequency Power supply type Energy efficiency scale	39.4 W 100 - 240 V 50 - 60 Hz Internal A to G
Colour gamut standard	sRGB	European Product Registry for Energy Labelling (EPREL) code	1406148
sRGB coverage (typical)	123%	Operational conditions	
NTSC coverage (typical)	107% ✓	Operating temperature (T-T)	0 - 40 °C
Display sRGB	*	Storage temperature (T-T)	-20 - 60 °C
Performance		Operating relative humidity (H-H)	20 - 80%
NVIDIA G-SYNC *	X	Operating altitude	0 - 3658 m
AMD FreeSync * Fast charging	X	Non-operating altitude	3658 - 12192 m
Fast charging technology	Power Delivery	Weight & dimensions	
VESA Adaptive Sync support	✓	Width (with stand)	1085 mm
Component video sync	Separate sync	Depth (with stand) Height (with stand)	238 mm 515 mm
Flicker-free technology	✓	Weight (with stand)	13 kg
Low Blue Light technology	✓	Width (without stand)	1085 mm
Multimedia		Depth (without stand)	158 mm
Number of speakers	2	Height (without stand)	337 mm
RMS rated power	10 W	Weight (without stand)	9.9 kg
Built-in speaker(s) *	✓	Packaging data	
Megapixel (approx.)	5 MP	Package width	1180 mm
Built-in microphone	√	Package depth	535 mm
Built-in camera *	*	Package height	235 mm
Design		Package weight	17.3 kg
Market positioning *	Business	Packaging content	
Product colour * Front bezel colour	Black Black	Stand included	✓
Feet colour	Black	Cables included	AC, DisplayPort, HDMI, USB Type-C to USB Type-A, USB Type-C to USB
Ports & interfaces			Type-C
Built-in USB hub *	✓	Manual Bundled software	✓ SmartControl
USB hub version	3.2 Gen 2 (3.1 Gen 2)		SmartControl
USB upstream port type	USB Type-C	Sustainability	
Number of upstream ports	2	Sustainability compliance	√
Number of USB Type-C upstream ports quantity	2	Sustainability certificates Doesn't contain	ENERGY STAR, TCO Mercury, PVC/BFR
USB Type-A downstream ports quantity	4	Other features	
USB Type-C downstream ports quantity	1	HBR3 support	Mac OS V Windows 11/10/9 1/9
USB Type-C DisplayPort Alternate Mode	✓	Compatible operating systems Picture-by-Picture (PbP)	Mac OS X Windows 11/10/8.1/8 ✓
USB Power Delivery	1	Exterior finish type	Textured
USB Power Delivery up to	100 W	Picture enhancement	SmartImage
HDMI *	✓	Recyclable packaging material	100%
HDMI ports quantity	2	Delta E	2
HDMI version	2.0	EasyRead mode LowBlue mode	√
DisplayPorts quantity	1	Philips SmartUniformity	93 - 105%
DisplayPort version	1.4		CE, Federal Communications
Audio output	√	Compliance certificates	Commission (FCC), RoHS
HDCP version	1 4/2 2	Mean time between failures (MTBF)	70000 h
HDCP version	1.4/2.2	Ethernet LAN data rates Wake-on-LAN	10,100,1000 Mbit/s ✓
		Recycling data	
		Post-consumer recycled plastic	85%
		1 000 consumer recycled plastic	J 70



8712581800970

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.