



GIGABYTE P750GM power supply unit 750 W 20+4 pin ATX ATX Black

Brand : GIGABYTE

Product code: GP-P750GM

Product name : P750GM


- 80 PLUS Gold certified
- Fully modular design
- 120mm Smart Hydraulic Bearing (HYB) Fan
- Main Japanese capacitors
- Powerful single +12V rail
- OVP/OPP/SCP/UV/OC/OTP protection
- 5 years warranty (Adjusted according to different regions)

P750GM, 80 PLUS Gold, 750W, Active PFC, 120mm

GIGABYTE P750GM. Total power: 750 W, AC input voltage: 100 - 240 V, AC input frequency: 50 - 60 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 61 cm, SATA power cable length: 150,600 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Cables included: CPU, PCIe, Peripheral (Molex), SATA



Power		Ports & interfaces	
Total power *	750 W	ATX power connector (20+4 pin)	✓
AC input voltage *	100 - 240 V	Floppy drive power connector	1
AC input frequency	50 - 60 Hz	Floppy disk drive cable length	12 cm
Input current	12-6 A	PCI Express connector	✓
Power Factor Correction (PFC) type	Active	Cabling type	Fully-Modular
Hold time	16 ms	Performance	
Efficiency	90%	80 PLUS certification *	80 PLUS Gold
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage	Purpose *	PC
Ports & interfaces		Power supply unit (PSU) form factor *	ATX
Motherboard power connector *	20+4 pin ATX	ATX version	2.31
Motherboard power cable length	61 cm	Mean time between failures (MTBF)	100000 h
Number of SATA power connectors	8	Design	
SATA power cable length	150,600 mm	Product colour	Black
Peripheral (Molex) power connectors (4-pin) *	4	Cooling type	Active
Peripheral (Molex) power cable length	120,500 mm	Fan diameter	12 cm
EPS power connector (4+4 pin)	✓	Number of fans	1 fan(s)
PCI Express power connectors (6+2 pin)	4	Fan location	Top
PCI Express power cable length	60 cm	Packaging content	
CPU power connector (4+4 pin)	✓	Cables included	CPU, PCIe, Peripheral (Molex), SATA
CPU power cable length	60 cm	Weight & dimensions	
		Width	150 mm
		Depth	140 mm
		Height	86 mm
Logistics data			
		Harmonized System (HS) code	84733020



0813567028710



813567028710



4719331551759

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.