



## ARCTIC F14 PWM PST CO 140mm PWM with PST Case Fan for Continuous Operation

**Brand :** ARCTIC

**Product code:** ACFAN00220A

**Product name :** F14 PWM PST CO 140mm PWM with PST Case Fan for Continuous Operation

- Japanese brand dual ball bearing provides a longer life span
  - Ideal for continuous operation with exceptional stability
  - PWM Sharing Technology (PST)
  - Extremely quiet with low noise impeller
  - High airflow and static pressure
- 140 mm PWM PST, 74 CFM, 126m<sup>3</sup>/h, 200 - 1350 RPM, 12V

**ARCTIC F14 PWM PST CO 140mm PWM with PST Case Fan for Continuous Operation:**

The F14 PWM PST CO fans aim to offer superior durability and cooling performance for demanding and continuous- operating PCs. With the PWM Sharing Technology (PST), the F14 PWM PST CO fans regulate the fan speed based on the actual needs with optimal cooling performance and noise control at all times. ARCTIC F14 PWM PST CO 140mm PWM with PST Case Fan for Continuous Operation. Type: Fan, Fan diameter: 14 cm, Rotational speed (min): 200 RPM, Rotational speed (max): 1350 RPM, Noise level (high speed): 24.5 dB, Noise level: 0.5 sone, Maximum airflow: 74 cfm, Airflow: 126 m<sup>3</sup>/h, Bearing type: Dual ball bearing. Voltage: 12 V. Width: 140 mm, Depth: 140 mm, Height: 27 mm. Product colour: Black



Performance		Design	
Suitable location *	Computer case	Number of fans	1 fan(s)
Type *	Fan	Fan connector	4-pin + 4-pin
Fan diameter	14 cm	<b>Power</b>	
Supported processor sockets	Not supported	Voltage	12 V
Compatible processor series	Not supported	Starting voltage	6 V
Rotational speed (min)	200 RPM	Fan voltage	12 V
Rotational speed (max)	1350 RPM	Fan current	0.3 A
Noise level (high speed)	24.5 dB	<b>Weight &amp; dimensions</b>	
Noise level	0.5 sone	Width	140 mm
Maximum airflow	74 cfm	Depth	140 mm
Airflow	126 m <sup>3</sup> /h	Height	27 mm
Pulse-width modulation (PWM) support	✓	Weight	183 g
Bearing type	Dual ball bearing	Cable length	0.4 m
Quantity per pack	1 pc(s)	Package width	143 mm
Fan static pressure	1.3 mmH <sub>2</sub> O	Package depth	29 mm
Operating temperature (T-T)	0 - 40 °C	Package height	143 mm
<b>Design</b>		<b>Packaging content</b>	
Product colour *	Black	Screws included	✓
Material	Plastic	<b>Logistics data</b>	
		Harmonized System (HS) code	84733080



4895213703031

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 03-NOV-2024. Prints or copies of Information are only valid on the printed Publication date