

[Product Website](#)[Experience in AR](#)

Energy-saving, ergonomic and reliable, the EV2781 shines with its picture quality. It receives the image signal, audio and USB data via its USB-C interface. The 70 W power delivery via USB-C is particularly practical. Here, notebooks can be connected and powered quickly and conveniently with just one cable. DisplayPort and HDMI inputs as well as four USB downstream ports complete the extensive connectivity options. This convenient multi-purpose connectivity simplifies a quick move when users use different workstations in the office or switch between office and home office. A picture-by-picture mode even allows simultaneous display of different signal sources. Useful when two computers are connected. The IPS LCD of the EV2781 offers a resolution of 2560 x 1440 pixels - this corresponds to a pixel density of 109 ppi for optimal readability. Matte anti-glare and Auto EcoView brightness control create a glare-free view, while sophisticated hybrid LCD backlight control ensures flicker-free viewing. The EV2781 can be rotated, swivelled and tilted in the way that is most comfortable for the back, neck and sitting posture. Its virtually bezel-less design provides a refined aesthetic. Controls, brightness sensor and speakers are integrated into the slim front bezel.

27" monitor with 2560 x 1440 pixels and fine 109 ppi resolution for excellent readability

Ideal connectivity thanks to USB-C interface with DisplayPort signal channel and power supply up to 70 watts

Only 1 mm housing frame: super-compact and ultra-chic design

Flicker-free image reproduction through hybrid control of image brightness

Auto EcoView and EcoView Optimizer for maximum energy savings and ideal ergonomics

Optimum anti-reflective coating and flexible positioning

USB hub version 3.1 with one USB-C upstream and four USB-A downstream ports

Signal inputs: USB-C (DisplayPort Alt Mode), DisplayPort, HDMI

Demonstrably environmentally and socially responsible production

5-year warranty for highest investment security

Technical Data

| GENERAL | | FEATURES & OPERATION | |
|---|---|--|---|
| Item no. | EV2781-BK EV2781-WT | USB-C docking | |
| Case color | Black White | Preset color/greyscale modes | 2x manual memory locations, sRGB, Paper, Movie, DICOM |
| Areas of application | Office | DICOM tone curve | |
| Product line | FlexScan | Auto EcoView | |
| Areas of application | Large and medium-sized companies, Private user & small business, Home Office, CAD, Finance, Control rooms | EcoView Index | |
| Specific system requirements | None, compatible with most computers and operating systems including macOS and Windows | EcoView Optimizer | |
| EAN | 4995047063438 4995047063445 | Overdrive | |
| | | No flickering | |
| | | HDCP Decoder | |
| | | Automatic signal input recognition | |
| | | Imagen por imagen | |
| | | Built-in speakers | |
| | | On-screen menu languages | de, en, fr, es, it, se |
| | | Adjustment options | Color Mode, Brightness, Contrast, Color temperature /White point, Gamma, Overdrive, Colour tone, Color saturation, Picture-by-Picture, Resolution, Scaling, OSD language, Signal input, All EcoView functions, Volume |
| | | Button Guide | |
| | | Integrated power unit | |
| SCREEN | | ELECTRICAL DATA | |
| Screen size [in inches] | 27 | Frequency | USB-C: 31-89 kHz/59-61 Hz; DisplayPort: 31-89 kHz/59-61 Hz; HDMI: 31-89 kHz/ 49-51 Hz/59-61 Hz |
| Screen size [in cm] | 68.5 | Power consumption (typical) [in watts] | 18 |
| Format | 16:9 | Maximum Power Consumption [in watts] | 153 (at maximum brightness with all signal inputs and USB ports in use) |
| Viewable image size (width x height) [in mm] | 597 x 336 | Max. Power consumption in stand-by mode [in watts] | 0.5 |
| Ideal and recommended resolution | 2560 x 1440 | Power consumption with power switch off [in watts] | 0 |
| Pixel pitch [in mm] | 0.233 x 0.233 | Energy efficiency class | D |
| Pixel density [in ppi] | 109 | Energy consumption/1000h [in kWh] | 17 |
| Supported resolutions | 2560 x 1440, 1920 x 1200, 1920 x 1080 (Full HD), 1680 x 1050, 1600 x 1200, 1280 x 1024, 1024 x 768, 800 x 600, 720 x 400, 640 x 480 | Power supply | AC 100-120 V / 200-240 V, 50/60 Hz |
| Panel technology | IPS | Max. USB-C Power Delivery [in Watt] | 70 |
| Max. viewing angle horizontal | 178 | Power management | |
| Max. viewing angle vertical | 178 | | |
| Number of colors or greyscale | 16.7 million colors (DisplayPort, 8 Bit), 16.7 million colors (HDMI, 8 Bit), 16.7 million colors (USB-C, 8 Bit) | | |
| Color palette/look-up table | More than 1.06 billion color tones /14-bit | | |
| Max. color space (typical) | sRGB | | |
| Max. brightness (typical) [in cd/m] | 350 | | |
| Max. dark room contrast (typical) | 1000:1 | | |
| Response time grey-grey alternation (typical) [in ms] | 5 | | |
| Backlight | LED | | |
| CONNECTIONS | | | |
| Signal inputs | USB-C (DisplayPort Alt Mode, HDCP 1.3), DisplayPort (HDCP 1.3), HDMI (HDCP 1.4) | | |
| USB specification | USB 5Gbps (USB 3) | | |
| USB upstream ports | 1 x type C (DisplayPort Alt Mode, 70 W max.) | | |
| USB downstream ports | 4x type A | | |
| Graphic signal | USB-C, DisplayPort, HDMI (RGB, YUV) | | |
| Audio input | USB-C, DisplayPort, HDMI | | |
| Audio / headphone output | 3.5 mm stereo jack | | |

DIMENSIONS & WEIGHT

| | |
|---|---|
| Dimensions (incl. stand) (width x height x depth) [in mm] | 611 x (369 - 545) x 230 |
| Weight (incl. stand) [in kg] | 8.5 |
| Dimensions (without stand) (width x height x depth) [in mm] | 611 x 357 x 56 |
| Weight (without stand) [in kg] | 5.7 |
| Dimension drawing (PDF) | Dimension drawing (PDF) |
| Rotatability of the stand [in °] | 344 |
| Tiltability forwards/backwards [in °] | 5 / 35 |
| Pivot between portrait / landscape | clockwise and anti-clockwise |
| Height adjustment range [in mm] | 176.6 |
| Hole spacing | 100 x 100 |

CERTIFICATION & STANDARDS

| | |
|---------------|---|
| Certification | CE, CB, TÜV/GS, TÜV/Ergonomics (including ISO 9241-307), TCO Certified Generation 9, EPEAT 2018 (US), TÜV/Blue Low Light Content, TÜV/Flicker Free, RCM, cTUVus, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA ENERGY STAR, RoHS, WEEE, China RoHS, CCC, EAC |
| EPEAT | EPEAT 2018 Gold (US), EPEAT Climate + |

SOFTWARE & ACCESSORIES

| | |
|--|--|
| Accompanying software and other accessories are available for download | Screen InStyle |
| Other box contents | USB/signal cable (USB-C - USB-C), Manual via download, Power cord, Quick guide |
| Accessories | PM200-K, CP200, HH200PR-K, CC100, PP100-K, PP200-K, PCSK-03 |

WARRANTY

| | |
|-------------------|---|
| Warranty periode | 5 years for unit and LCD module up to 30,000 operating hours, whichever comes first. |
| Included warranty | Zero pixel defects guarantee: no fully illuminated sub-pixels (sub-pixels ISO 9241-307) for six months from date of purchase. |



Experience the
EV2781 in AR now!

Find your EIZO contact:
EIZO Europe GmbH
Belgrader Straße 2
41069 Mönchengladbach
Phone: +49 2161 8210-0
www.eizo.eu

All product names are trademarks or registered trademarks of EIZO Corporation in Japan and other countries or their respective companies. Copyright © 2024 EIZO Europe GmbH, Belgrader Str. 2, 41069 Mönchengladbach, Germany. All rights, errors and modifications reserved. Latest update: 16.07.2024