

APC Netshelter Rack Automatic Transfer Switch, 1U, 10A, 230V, C14 IN, 12 C13 OUT, 50/60Hz

AP4421A

Call for More Information 0800 2799254



- Includes: Mounting hardware, Rack mounting brackets, Serial configuration cable

Output	
Always on Outlets	12
Overload Protection	No

Input	
Input frequency	50/60 Hz
Input Connections	IEC 60320 C14 10 A 2P + E
Acceptable Input Voltage	207 - 253VAC
Load Capacity	2000VA
Maximum Line Current	10A
Regulatory Derated Input Current (North America)	10A

Physical	
Maximum Height	44MM, 4.4CM
Maximum Width	432MM, 43.2CM
Maximum Depth	236MM, 23.6CM
Rack Height	1U
Net Weight	3.93KG
Color	Black

Environmental	
Operating Temperature	-5 - 45 °C

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Environmental	
Operating Relative Humidity	5 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Relative Humidity	5 - 95 %
Storage Elevation	0 - 15240meters
Conformance	
Approvals	EN 55022 class A, FCC part 15 class A
Standard warranty	2 years repair or replace
Sustainable Offer Status	
RoHS	Compliant
Other Environmental Compliance	China RoHS

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.