



USB Event Monitoring Utility: Track and log connected USB devices.

For more information and to download the StarTech.com Connectivity Tools application, please visit:  
[www.startech.com/connectivity-tools](http://www.startech.com/connectivity-tools)

This product is backed for 3-years by StarTech.com, including free lifetime 24/5 multi-lingual technical assistance.

## Certifications, Reports and Compatibility



## Applications

- Ideal for deployment in business and education environments with automatic firmware updates available through ChromeOS
- Travel between the home and office

## Features

- **5-IN-1 MULTIPORT ADAPTER:** Portable USB-C travel dock supports UHD 4K 60Hz HDMI 2.0b (HDR10) video via DP 1.4 Alt Mode for connecting a monitor/display, 3-port USB-A hub (2x USB 2.0 480Mbps & 1x USB 3.2 Gen 1 5Gbps), 100W USB-C Power Delivery Pass-Through
- **WORKS WITH CHROMEBOOK:** WWCB certified for compatibility with all Chromebooks and ideal for ChromeOS Enterprise Devices; Also works w/Windows & macOS USB-C, TB3, TB4 PCs; Auto firmware updates through ChromeOS for max performance, compatibility & security
- **EXTRA-LONG CABLE:** Extended port reach w/attached 12" host cable, clip for cable management, automatic driver setup, weighted design to keep adapter more stable on work surface, ideal for office or work-from-home workstations & presenting from a boardroom
- **RELIABLE PERFORMANCE:** 100W Power Delivery Pass-Through with 14W reserved for adapter (when using one or all ports) and up to 86W available for host laptop charging; Prevents device dropouts, video flickering, and/or power overdraw common in other hubs
- **USB PORTS WITH DEDICATED POWER:** With a USB-C power adapter connected to the mini dock, each downstream USB-A port provides dedicated power (USB 3.2 5Gbps: 4.5W / USB 2.0: 2.5W), ideal for connecting USB devices that require a consistent power draw

---

## Hardware



Warranty	3 Years
4K Support	Yes
Fast-Charge Port(s)	No
Displays Supported	1
Interface	USB 3.2 Gen 1 (5Gbps)
Bus Type	USB-C
Industry Standards	HDMI 2.0b
	USB 3.2 Gen 1 (5Gbps)
	USB Power Delivery Specification Rev. 3.0
	Certified Works with ChromeBook (WWCB)
Chipset ID	Analogix - ANX7327
	Analogix - ANX7518
	VIA - VL817-Q7

---

### Performance

Maximum Data Transfer Rate	5Gbps
Maximum Digital Resolutions	Up to 4K (4096x2160) 60Hz
Type and Rate	USB 3.2 Gen 1 - 5 Gbit/s
UASP Support	Yes
General Specifications	Maximum Laptop Charging: 86W

---

### Connector(s)

External Ports	1 - HDMI (19 pin)
	1 - USB 3.2 Type-A (9 pin, Gen 1, 5Gbps)
	2 - USB 2.0 Type-A (4 pin, 480Mbps)
	1 - USB Type-C (24 pin) USB Power Delivery Only
Host Connectors	1 - USB 3.2 Type-C (24 pin, Gen 1, 5Gbps)

---



## Software

OS Compatibility	Windows 10, 11 >macOS 10.15, 11.0, 12.0, 13.0 >Android >Linux Ubuntu 18.04, 20.04 >ChromeOS (Certified Works with Chromebook)
------------------	--

## Special Notes / Requirements

System and Cable Requirements	<p>A host device with an available USB-C port (to ensure full adapter functionality, the host device's USB-C port must support USB Power Delivery 2.0 and DP alt mode).</p> <p>Optional: USB-C power adapter (for example, your laptop's USB-C based power adapter).</p>
Note	<p>Not all USB-C ports support the full functionality of the USB Type-C standard. Ensure that your host USB-C port supports USB Power Delivery and DP alt mode.</p> <p>If the USB-C Host does not support USB Power Delivery, the PD Power Port will not supply power to the USB-C Host.</p> <p>A 4K-capable display is required to achieve UHD resolution (4K is also known as 4K x 2K).</p> <p>USB 3.2 Gen 1 (5Gbps) is also known as USB 3.1 Gen 1 (5Gbps) and USB 3.0 (5Gbps).</p> <p>Your laptop might have specific charging requirements. For example, if your laptop requires exactly 60W of power and an adapter consumes some of the 60W, your laptop might not recognize that it is getting enough power. For more information about Power Delivery, refer to the manufacturer of your hardware.</p>

## Power

Power Source	Bus Powered and Host USB-C Power Adapter
Power Delivery	100W
Power Consumption (In Watts)	14W

## Environmental

Operating Temperature	0C to 35C (32F to 95F)
Storage Temperature	-25C to 65C (-13F to 149F)
Humidity	0~95% RH (Non-condensing)

## Physical Characteristics



Color	Space Gray
Material	Plastic
Cable Length	13.8 in [35 cm]
Product Length	3.9 in [10.0 cm]
Product Width	1.9 in [4.8 cm]
Product Height	0.6 in [1.6 cm]
Weight of Product	3.7 oz [105.0 g]

---

**Packaging Information**

Package Length	7.1 in [18.0 cm]
Package Width	4.5 in [11.5 cm]
Package Height	1.6 in [4.0 cm]
Shipping (Package) Weight	4.2 oz [120.0 g]

---

**What's in the Box**

Included in Package	1 - USB-C Multiport Adapter
	1 - Quick-Start Guide

---

***\*Product appearance and specifications are subject to change without notice.***

